

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 9
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176308 (0) DR 1
B Z 分類	B Z 3

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	54	46	41	37	53	46	40	37	52	45	40	37	50	44	40	36	35
			0.63	0.8	62	55	49	46	61	54	49	45	59	53	49	45	58	52	48	45	44
			0.56	1.0	67	60	55	51	66	60	55	51	64	58	54	51	62	57	54	51	49
				1.25	71	65	61	57	70	65	60	57	68	63	59	56	66	62	59	56	54
下方投影面積		cm ²		1.5	74	69	64	61	73	68	64	61	71	67	63	60	69	65	62	60	58
			等価発光面積	cm ²	2.0	78	73	70	66	77	73	69	66	75	71	68	65	73	70	67	65
取付 高さ	器具間隔最大限			2.5	80	76	73	70	79	75	72	70	77	74	71	69	75	72	70	68	66
	横方向 (A) 縦方向 (B)			3.0	82	78	75	73	81	77	75	72	78	76	74	71	76	74	72	71	69
H m	1.39 H m 1.39 H m			4.0	84	81	79	77	83	80	78	76	80	78	77	75	78	77	75	74	72
				5.0	85	83	81	79	84	82	80	78	82	80	78	77	80	78	77	76	74
				7.0	86	85	83	82	85	84	82	81	83	82	81	80	81	80	79	78	76
				10.0	87	86	85	84	86	85	84	83	84	83	82	82	82	81	81	80	78

