

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 9
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184503 (0) DR 1
B Z 分類	BZ3 / 0.7 / BZ2 / 1.8 / BZ3

器具効率		69 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 69 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	45	39	34	31	45	38	34	31	43	38	34	31	42	37	33	31	30	
			0.63	0.8	52	46	41	38	51	45	41	38	49	44	41	38	48	44	40	38	37	
			1.0	56	50	46	43	55	50	46	43	53	49	45	43	52	48	45	42	41		
			0.56	1.25	59	54	51	48	58	54	50	47	57	53	50	47	55	52	49	47	45	
下方投影面積		cm ²	1.5	62	57	54	51	61	57	53	51	59	55	52	50	57	54	52	50	48		
等価発光面積		cm ²	2.0	65	61	58	55	64	60	57	55	62	59	57	54	60	58	56	54	52		
取付 高さ	器具間隔最大限		2.5	67	63	61	58	66	63	60	58	64	61	59	57	62	60	58	57	55		
	横方向 (A) 縦方向 (B)		3.0	68	65	63	61	67	64	62	60	65	63	61	59	64	62	60	59	57		
H m	1.39 H m	1.39 H m	4.0	69	67	65	64	68	66	65	63	67	65	64	62	65	64	62	61	60		
			5.0	70	69	67	65	69	68	66	65	68	66	65	64	66	65	64	63	61		
			7.0	71	70	69	68	71	69	68	67	69	68	67	66	67	66	66	65	63		
			10.0	72	71	70	70	71	71	70	69	70	69	68	68	68	68	67	66	65		

