

屋内照明器具特性

品番 (品名)	XND0631WW									
光源	LED4000_85_620 x1					620.0 lm				
管理番号	K0158840(5)DB1									
BZ分類	BZ2/0.7/BZ1/4.5/BZ2/6.0/BZ1									

器具効率	100%	天井	80%				70%				50%				30%				0%			
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
下方光束	100%	床	10%				10%				10%				10%				0%			
室指数			照明率 (X0.01)																			
保守率	良	0.81	0.6	71	62	56	52	70	61	56	52	68	60	55	52	66	60	55	52	50		
	中	0.77	0.8	80	73	67	63	79	72	67	63	77	71	66	63	76	70	66	63	61		
	否	0.68	1.0	86	79	74	70	85	79	74	70	83	77	73	70	81	76	73	70	68		
			1.25	91	85	80	77	90	84	80	76	88	83	79	76	86	81	78	75	74		
下方投影面積		cm ²	1.5	94	88	84	81	93	88	84	81	90	86	83	80	88	85	82	79	78		
等価発光面積		cm ²	2.0	98	93	90	87	96	92	89	86	94	91	88	85	92	89	87	85	83		
取付高さ	器具間隔最大限		2.5	100	96	93	91	99	95	92	90	96	94	91	89	94	92	90	88	86		
	横方向 (A)	縦方向 (B)	3.0	101	98	95	93	100	97	95	93	98	95	93	91	96	94	92	90	88		
Hm	1.27Hm	1.27Hm	4.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	93	91		
			5.0	104	102	100	99	103	101	100	98	101	99	98	97	99	97	96	95	93		
			7.0	106	104	103	101	104	103	102	101	102	101	100	99	100	99	98	97	95		
			10.0	106	105	104	103	105	104	103	102	103	102	101	101	100	100	99	99	96		

