

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 9
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 5 1 4 (0) D R 1
B Z 分類	B Z 3

器具効率		7 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 0	4 2	3 7	3 4	4 9	4 2	3 7	3 4	4 8	4 1	3 7	3 4	4 6	4 0	3 6	3 4	3 2
			0 . 6 3	0 . 8	5 7	5 0	4 5	4 2	5 6	5 0	4 5	4 2	5 5	4 9	4 5	4 2	5 3	4 8	4 4	4 1	4 0
			0 . 5 6	1 . 0	6 2	5 5	5 1	4 7	6 1	5 5	5 1	4 7	5 9	5 4	5 0	4 7	5 7	5 3	4 9	4 7	4 5
				1 . 2 5	6 6	6 0	5 6	5 2	6 5	5 9	5 5	5 2	6 3	5 8	5 5	5 2	6 1	5 7	5 4	5 1	5 0
下方投影面積		c m ²	1 . 5	6 8	6 3	5 9	5 6	6 7	6 3	5 9	5 6	6 5	6 1	5 8	5 5	6 3	6 0	5 7	5 5	5 3	
			等価発光面積	2 . 0	7 2	6 8	6 4	6 1	7 1	6 7	6 4	6 1	6 9	6 5	6 3	6 0	6 7	6 4	6 2	6 0	5 8
取付 高さ	器具間隔最大限		2 . 5	7 4	7 0	6 7	6 5	7 3	6 9	6 7	6 4	7 1	6 8	6 6	6 3	6 9	6 7	6 5	6 3	6 1	
	横方向 (A) 縦方向 (B)		3 . 0	7 5	7 2	6 9	6 7	7 4	7 1	6 9	6 7	7 2	7 0	6 8	6 6	7 0	6 8	6 7	6 5	6 3	
H m	1 . 3 9 H m 1 . 3 9 H m		4 . 0	7 7	7 5	7 2	7 0	7 6	7 4	7 2	7 0	7 4	7 2	7 0	6 9	7 2	7 1	6 9	6 8	6 6	
			5 . 0	7 8	7 6	7 4	7 3	7 7	7 5	7 4	7 2	7 5	7 4	7 2	7 1	7 3	7 2	7 1	7 0	6 8	
			7 . 0	7 9	7 8	7 6	7 5	7 8	7 7	7 6	7 5	7 6	7 5	7 4	7 3	7 5	7 4	7 3	7 2	7 0	
			1 0 . 0	8 0	7 9	7 8	7 7	7 9	7 8	7 7	7 7	7 7	7 7	7 6	7 5	7 6	7 5	7 4	7 4	7 2	

