

屋内照明器具特性	
品番 (品名)	L G B 1 5 1 1 8
光源	LLD3000CU1 ×1 795.0 lm
管理番号	K0179049 (0) DR 1
B Z 分類	BZ3 / 4.5 / BZ4

器具効率		78 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01)																	Z
保守率	良 中 否	0.67	0.6	50	42	37	33	49	42	37	33	48	41	37	33	46	40	36	33	32		
		0.63	0.8	57	50	45	41	56	49	44	41	55	48	44	41	53	47	44	40	39		
		0.56	1.0	62	55	50	46	61	54	50	46	59	53	49	46	57	52	48	45	44		
			1.25	66	60	55	51	65	59	55	51	63	58	54	51	61	57	53	50	49		
下方投影面積		cm ²		1.5	69	63	58	55	67	62	58	55	65	61	57	54	63	60	56	54	52	
等価発光面積			cm ²	2.0	72	68	64	60	71	67	63	60	69	65	62	59	67	64	61	59	57	
取付 高さ	器具間隔最大限			2.5	75	71	67	64	73	70	67	64	71	68	65	63	69	67	64	62	60	
	横方向 (A)			縦方向 (B)	3.0	76	73	70	67	75	72	69	66	73	70	68	66	71	69	67	65	63
H m	1.32 H m	1.32 H m		4.0	78	75	73	71	77	74	72	70	75	73	71	69	73	71	70	68	66	
			5.0	79	77	75	73	78	76	74	72	76	74	73	71	74	73	71	70	68		
			7.0	81	79	77	76	80	78	77	75	78	76	75	74	76	75	74	73	71		
			10.0	82	81	79	78	81	80	79	78	79	78	77	76	77	76	76	75	73		

