

屋内照明器具特性	
品番 (品名)	LGB15118
光源	LLD2020CU1 ×1 468.0 lm
管理番号	K0179070 (0) DR1
BZ分類	BZ1

器具効率		9 6 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		9 6 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束																						
保守率		良 中 否	0 . 6	8 2	7 7	7 3	7 1	8 2	7 7	7 3	7 1	8 0	7 6	7 3	7 1	7 9	7 5	7 3	7 1	7 0		
			0 . 6 3	0 . 8	8 7	8 2	7 9	7 7	8 7	8 2	7 9	7 7	8 5	8 1	7 8	7 6	8 4	8 1	7 8	7 6	7 5	
			1 . 0	9 0	8 6	8 3	8 0	9 0	8 6	8 3	8 0	8 8	8 5	8 2	8 0	8 7	8 4	8 1	8 0	7 8		
			0 . 5 6	1 . 2 5	9 3	8 9	8 6	8 4	9 2	8 9	8 6	8 4	9 1	8 7	8 5	8 3	8 9	8 6	8 4	8 3	8 1	
下方投影面積		c m ²	1 . 5	9 5	9 1	8 9	8 6	9 4	9 1	8 8	8 6	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 5	8 3		
			等価発光面積		c m ²	2 . 0	9 7	9 4	9 2	9 0	9 6	9 4	9 1	9 0	9 4	9 2	9 0	8 9	9 3	9 1	8 9	8 8
取付 高さ	器具間隔最大限		2 . 5	9 9	9 6	9 4	9 2	9 8	9 5	9 3	9 2	9 6	9 4	9 2	9 1	9 4	9 2	9 1	9 0	8 8		
	横方向 (A)		縦方向 (B)		3 . 0	9 9	9 7	9 6	9 4	9 8	9 7	9 5	9 3	9 6	9 5	9 3	9 2	9 5	9 3	9 2	9 1	8 9
H m	0 . 3 7 H m		0 . 3 7 H m		4 . 0	1 0 1	9 9	9 8	9 6	1 0 0	9 8	9 7	9 6	9 8	9 6	9 5	9 4	9 6	9 5	9 4	9 3	9 1
					5 . 0	1 0 1	1 0 0	9 9	9 8	1 0 0	9 9	9 8	9 7	9 8	9 7	9 6	9 5	9 6	9 5	9 5	9 4	9 2
					7 . 0	1 0 2	1 0 1	1 0 0	9 9	1 0 1	1 0 0	9 9	9 8	9 9	9 8	9 8	9 7	9 7	9 6	9 6	9 5	9 3
					1 0 . 0	1 0 3	1 0 2	1 0 1	1 0 1	1 0 2	1 0 1	1 0 0	1 0 0	1 0 0	9 9	9 8	9 8	9 8	9 7	9 7	9 6	9 4

