

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 3 8
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176318 (0) DR 1
B Z 分類	B Z 3

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	49	41	37	33	48	41	36	33	47	40	36	33	45	40	36	33	32
			0.63	0.8	55	48	44	40	55	48	43	40	53	47	43	40	51	46	42	40	38
			0.56	1.0	60	53	48	45	59	53	48	45	57	52	48	44	55	51	47	44	43
				1.25	63	57	53	50	62	57	53	49	60	56	52	49	59	55	51	49	47
下方投影面積		cm ²		1.5	66	61	56	53	65	60	56	53	63	59	55	52	61	57	54	52	50
				2.0	69	65	61	58	68	64	61	58	66	63	60	57	64	61	59	57	55
取付高さ	器具間隔最大限			2.5	71	68	64	62	70	67	64	61	68	65	63	61	66	64	62	60	58
	横方向 (A) 縦方向 (B)			3.0	73	70	67	64	72	69	66	64	70	67	65	63	68	66	64	62	60
H m	1.32 H m	1.32 H m		4.0	75	72	70	68	74	71	69	67	72	70	68	66	70	68	67	65	63
				5.0	76	74	72	70	75	73	71	70	73	71	70	68	71	70	69	67	65
				7.0	77	76	74	73	76	75	73	72	74	73	72	71	73	72	71	70	68
				10.0	78	77	76	75	77	76	75	74	75	75	74	73	74	73	72	72	69

