

屋内照明器具特性	
品番 (品名)	L G B 1 5 3 3 8
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 1 m
管理番号	K 0 1 8 4 5 0 2 (0) D R 1
B Z 分類	B Z 1

器具効率		8 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
上方光束		0 %		床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
下方光束		8 4 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	6 6	6 0	5 6	5 3	6 5	5 9	5 5	5 3	6 4	5 9	5 5	5 3	6 2	5 8	5 5	5 3	5 2		
			0 . 6 3	0 . 8	7 2	6 6	6 2	6 0	7 1	6 6	6 2	6 0	6 9	6 5	6 2	5 9	6 8	6 4	6 1	5 9	5 8		
			0 . 5 6	1 . 0	7 5	7 0	6 7	6 4	7 4	7 0	6 7	6 4	7 3	6 9	6 6	6 4	7 1	6 8	6 5	6 3	6 2		
			1 . 2 5	7 8	7 4	7 1	6 8	7 7	7 3	7 0	6 8	7 6	7 2	7 0	6 8	7 4	7 1	6 9	6 7	6 6			
下方投影面積		c m ²	1 . 5	8 0	7 7	7 3	7 1	7 9	7 6	7 3	7 1	7 8	7 5	7 2	7 0	7 6	7 4	7 1	7 0	6 8			
			等価発光面積	c m ²	2 . 0	8 3	8 0	7 7	7 5	8 2	7 9	7 7	7 5	8 0	7 8	7 6	7 4	7 9	7 7	7 5	7 3	7 2	
取付 高さ	器具間隔最大限		2 . 5	8 5	8 2	8 0	7 8	8 4	8 1	7 9	7 7	8 2	8 0	7 8	7 6	8 0	7 8	7 7	7 5	7 4			
	横方向 (A) 縦方向 (B)		3 . 0	8 6	8 3	8 1	7 9	8 5	8 2	8 1	7 9	8 3	8 1	7 9	7 8	8 1	8 0	7 8	7 7	7 5			
H m	0 . 7 4 H m	0 . 7 4 H m	4 . 0	8 7	8 5	8 3	8 2	8 6	8 4	8 3	8 1	8 4	8 3	8 1	8 0	8 2	8 1	8 0	7 9	7 7			
			5 . 0	8 8	8 6	8 5	8 4	8 7	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 3	8 2	8 1	8 0	7 8			
			7 . 0	8 9	8 7	8 6	8 5	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 3	8 4	8 3	8 3	8 2	8 0			
			1 0 . 0	8 9	8 8	8 8	8 7	8 8	8 8	8 7	8 6	8 6	8 6	8 5	8 5	8 5	8 4	8 4	8 3	8 1			

