

屋内照明器具特性	
品番 (品名)	L G B 1 6 7 4 8
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 2 0 (0) D R 1
B Z 分類	B Z 3

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	41	35	31	28	40	34	31	28	39	34	30	28	38	33	30	28	27
			0 . 6 3	0 . 8	47	41	37	34	46	40	36	34	44	39	36	33	43	39	36	33	32
			0 . 5 6	1 . 0	50	45	41	38	49	44	40	38	48	43	40	37	46	42	39	37	36
				1 . 2 5	53	48	45	42	52	48	44	42	51	47	44	41	49	46	43	41	40
下方投影面積		c m ²	1 . 5	55	51	47	45	54	50	47	44	53	49	46	44	51	48	46	44	42	
			等価発光面積	2 . 0	58	55	51	49	57	54	51	49	56	53	50	48	54	52	49	48	46
取付 高さ	器具間隔最大限		2 . 5	60	57	54	52	59	56	54	52	57	55	53	51	56	54	52	50	49	
	横方向 (A)	縦方向 (B)	3 . 0	61	59	56	54	60	58	56	54	59	57	55	53	57	55	54	52	51	
H m	1 . 3 2 H m	1 . 3 2 H m	4 . 0	63	61	59	57	62	60	58	57	60	59	57	56	59	57	56	55	53	
			5 . 0	64	62	60	59	63	61	60	58	61	60	59	57	60	59	58	57	55	
			7 . 0	65	64	62	61	64	63	62	61	63	61	61	60	61	60	59	59	57	
			1 0 . 0	66	65	64	63	65	64	63	62	63	63	62	61	62	61	61	60	58	

