

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 0
光源	L L D 4 0 0 0 1 C Q 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 2 8 4 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 6 . 0 / B Z 3

器具効率		7 9 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																Z C M
保守率		良 中 否	0 . 6 7	0 . 6	4 6	3 7	3 1	2 7	4 5	3 6	3 1	2 7	4 3	3 6	3 0	2 6	4 2	3 5	3 0	2 6	2 5
			0 . 6 3	0 . 8	5 5	4 6	4 0	3 6	5 3	4 5	4 0	3 6	5 1	4 4	3 9	3 5	4 9	4 3	3 9	3 5	3 3
			0 . 5 6	1 . 0	6 0	5 2	4 6	4 2	5 9	5 1	4 6	4 2	5 7	5 0	4 5	4 2	5 5	4 9	4 5	4 1	4 0
				1 . 2 5	6 5	5 8	5 3	4 8	6 4	5 7	5 2	4 8	6 1	5 6	5 1	4 8	5 9	5 5	5 1	4 7	4 6
下方投影面積		c m ²	1 . 5	6 8	6 2	5 7	5 3	6 7	6 1	5 7	5 3	6 5	6 0	5 6	5 2	6 3	5 8	5 5	5 2	5 0	
			2 . 0	7 3	6 8	6 3	6 0	7 2	6 7	6 3	6 0	6 9	6 5	6 2	5 9	6 7	6 4	6 1	5 8	5 6	
取付 高さ	器具間隔最大限		2 . 5	7 5	7 1	6 7	6 4	7 4	7 0	6 7	6 4	7 2	6 9	6 6	6 3	7 0	6 7	6 5	6 2	6 0	
	横方向 (A)	縦方向 (B)	3 . 0	7 7	7 3	7 0	6 8	7 6	7 3	7 0	6 7	7 4	7 1	6 8	6 6	7 2	6 9	6 7	6 5	6 3	
H m	1 . 2 8 H m	1 . 2 8 H m	4 . 0	7 9	7 7	7 4	7 2	7 8	7 6	7 3	7 1	7 6	7 4	7 2	7 0	7 4	7 2	7 1	6 9	6 7	
			5 . 0	8 1	7 8	7 6	7 4	8 0	7 7	7 5	7 4	7 8	7 6	7 4	7 2	7 6	7 4	7 3	7 1	6 9	
			7 . 0	8 2	8 0	7 9	7 7	8 1	8 0	7 8	7 7	7 9	7 8	7 7	7 5	7 7	7 6	7 5	7 4	7 2	
			1 0 . 0	8 3	8 2	8 1	8 0	8 2	8 1	8 0	7 9	8 0	7 9	7 8	7 8	7 8	7 8	7 7	7 6	7 4	

