

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 0
光源	L L D 2 0 0 0 C U 1 × 1 5 6 6 . 0 l m
管理番号	K 0 1 7 9 0 4 5 (0) D R 1
B Z 分類	B Z 5 / 0 . 9 / B Z 4

器具効率		9 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		9 3 %																					
保守率		良 中 否	0 . 6 7	0 . 6	5 4	4 2	3 5	3 0	5 2	4 2	3 5	3 0	5 0	4 1	3 4	3 0	4 8	4 0	3 4	3 0	2 8		
			0 . 6 3	0 . 8	6 3	5 3	4 6	4 0	6 2	5 2	4 5	4 0	5 9	5 1	4 5	4 0	5 7	5 0	4 4	4 0	3 8		
			0 . 5 6	1 . 0	7 0	6 0	5 3	4 8	6 8	5 9	5 3	4 8	6 6	5 8	5 2	4 7	6 3	5 6	5 1	4 7	4 5		
				1 . 2 5	7 6	6 7	6 0	5 5	7 4	6 6	6 0	5 5	7 1	6 4	5 9	5 5	6 9	6 3	5 8	5 4	5 2		
下方投影面積		c m ²	1 . 5	8 0	7 2	6 6	6 1	7 8	7 1	6 5	6 0	7 5	6 9	6 4	6 0	7 3	6 7	6 3	5 9	5 7			
等価発光面積		c m ²	2 . 0	8 5	7 9	7 3	6 9	8 3	7 8	7 3	6 9	8 1	7 6	7 1	6 8	7 8	7 4	7 0	6 7	6 5			
取付 高さ	器具間隔最大限		2 . 5	8 8	8 3	7 8	7 4	8 7	8 2	7 8	7 4	8 4	8 0	7 6	7 3	8 2	7 8	7 5	7 2	7 0			
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 6	8 2	7 8	8 9	8 5	8 1	7 8	8 6	8 3	8 0	7 7	8 4	8 1	7 8	7 6	7 3			
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	9 3	9 0	8 6	8 4	9 2	8 9	8 6	8 3	8 9	8 6	8 4	8 2	8 7	8 5	8 2	8 0	7 8			
			5 . 0	9 5	9 2	8 9	8 7	9 4	9 1	8 8	8 6	9 1	8 9	8 7	8 5	8 9	8 7	8 5	8 3	8 1			
			7 . 0	9 7	9 5	9 3	9 1	9 5	9 3	9 2	9 0	9 3	9 1	9 0	8 8	9 1	8 9	8 8	8 7	8 4			
			1 0 . 0	9 8	9 7	9 5	9 4	9 7	9 5	9 4	9 3	9 5	9 3	9 2	9 1	9 2	9 1	9 0	8 9	8 7			

