

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 0
光源	L L D 4 0 4 0 2 C Q 1 (S H U K O U) × 1 6 2 0 . 0 1 m
管理番号	K 0 1 8 4 4 8 5 (0) D R 1
B Z 分類	B Z 1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		88 %																									
保守率		良	0.67	0.6	67	61	56	53	67	60	56	53	65	60	56	53	64	59	56	53	52						
		中	0.63	0.8	74	68	64	61	73	68	64	61	72	67	63	61	70	66	63	60	59						
		否	0.56	1.0	78	73	69	66	77	72	69	66	76	71	68	66	74	70	68	65	64						
				1.25	82	77	73	71	81	76	73	70	79	75	72	70	77	74	72	70	68						
下方投影面積		cm ²		1.5	84	80	77	74	83	79	76	74	81	78	75	73	79	77	74	73	71						
等価発光面積		cm ²		2.0	87	83	81	78	86	83	80	78	84	81	79	77	82	80	78	77	75						
取付高さ	器具間隔最大限			2.5	89	86	83	81	88	85	83	81	86	83	82	80	84	82	80	79	77						
	横方向 (A)		縦方向 (B)	3.0	90	87	85	83	89	86	84	83	87	85	83	82	85	83	82	81	79						
H _m	0.73 H _m		0.73 H _m	4.0	91	89	87	86	90	88	87	85	88	87	85	84	86	85	84	83	81						
				5.0	92	90	89	88	91	89	88	87	89	88	87	86	87	86	85	84	82						
				7.0	93	92	91	90	92	91	90	89	90	89	88	87	88	87	87	86	84						
				10.0	94	93	92	91	93	92	91	90	91	90	89	89	89	88	88	87	85						

