

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 0
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 2 8 5 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 6 . 0 / B Z 3

器具効率	9 0 % 上方光束 0 % 下方光束 9 0 %	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
		反射率	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
		室指数	照明率 (X 0 . 0 1) Z C M																
保守率	良 0 . 6 7	0 . 6	5 3	4 2	3 5	3 0	5 2	4 2	3 5	3 0	4 9	4 1	3 5	3 0	4 8	4 0	3 4	3 0	2 8
	中 0 . 6 3	0 . 8	6 2	5 2	4 6	4 1	6 1	5 2	4 5	4 1	5 9	5 0	4 5	4 0	5 6	4 9	4 4	4 0	3 8
	否 1 . 0	1 . 0	6 9	5 9	5 3	4 8	6 7	5 9	5 3	4 8	6 5	5 7	5 2	4 8	6 2	5 6	5 1	4 7	4 5
	0 . 5 6	1 . 2 5	7 4	6 6	6 0	5 5	7 3	6 5	6 0	5 5	7 0	6 4	5 9	5 5	6 8	6 2	5 8	5 4	5 2
下方投影面積 等価発光面積	c m ² c m ²	1 . 5	7 8	7 1	6 5	6 1	7 7	7 0	6 5	6 0	7 4	6 8	6 4	6 0	7 1	6 7	6 3	5 9	5 7
		2 . 0	8 3	7 7	7 2	6 8	8 2	7 6	7 2	6 8	7 9	7 4	7 1	6 7	7 7	7 3	6 9	6 7	6 4
		2 . 5	8 6	8 1	7 7	7 3	8 5	8 0	7 6	7 3	8 2	7 8	7 5	7 2	8 0	7 7	7 4	7 1	6 9
		3 . 0	8 8	8 4	8 0	7 7	8 7	8 3	7 9	7 7	8 4	8 1	7 8	7 5	8 2	7 9	7 7	7 4	7 2
取付高さ	器具間隔最大限 横方向 (A) 縦方向 (B)	4 . 0	9 1	8 7	8 4	8 2	8 9	8 6	8 4	8 1	8 7	8 4	8 2	8 0	8 5	8 2	8 1	7 9	7 6
H m	1 . 2 8 H m 1 . 2 8 H m	5 . 0	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 4	8 8	8 6	8 4	8 3	8 6	8 4	8 3	8 1	7 9
		7 . 0	9 4	9 2	9 0	8 8	9 3	9 1	8 9	8 7	9 0	8 9	8 7	8 6	8 8	8 7	8 6	8 4	8 2
		1 0 . 0	9 5	9 4	9 2	9 1	9 4	9 3	9 1	9 0	9 2	9 0	8 9	8 8	8 9	8 9	8 8	8 7	8 4

