

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 1
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0176282 (0) DR 1
B Z 分類	BZ5 / 0.7 / BZ4 / 6.0 / BZ3

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X0.01) Z C M															
保守率		良 中 否	0.67	0.6	43	34	28	25	42	34	28	25	40	33	28	24	39	32	28	24	23	
			0.63	0.8	50	42	37	33	49	42	37	33	47	41	36	33	46	40	36	32	31	
			0.56	1.0	56	48	43	39	54	48	43	39	52	46	42	38	50	45	41	38	37	
				1.25	60	54	49	45	59	53	48	45	57	52	48	44	55	50	47	44	42	
下方投影面積		c m ²		1.5	63	57	53	49	62	57	52	49	60	55	52	48	58	54	51	48	46	
			等価発光面積	2.0	67	63	59	55	66	62	58	55	64	60	57	55	62	59	56	54	52	
取付 高さ	器具間隔最大限			2.5	70	66	62	60	69	65	62	59	67	63	61	58	65	62	60	58	56	
	横方向 (A) 縦方向 (B)			3.0	71	68	65	62	70	67	64	62	68	66	63	61	66	64	62	60	59	
H m	1.28 H m	1.28 H m		4.0	73	71	68	66	72	70	68	66	70	68	66	65	69	67	65	64	62	
				5.0	75	72	70	69	74	72	70	68	72	70	68	67	70	68	67	66	64	
				7.0	76	74	73	72	75	74	72	71	73	72	71	70	71	70	69	68	66	
				10.0	77	76	75	74	76	75	74	73	74	73	73	72	73	72	71	70	68	

