

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 4
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 6 2 8 5 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4 / 6 . 0 / B Z 3

器具効率		9 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		0 % 9 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 2	3 5	3 0	5 2	4 2	3 5	3 0	4 9	4 1	3 5	3 0	4 8	4 0	3 4	3 0	2 8	
			0 . 6 3	0 . 8	6 2	5 2	4 6	4 1	6 1	5 2	4 5	4 1	5 9	5 0	4 5	4 0	5 6	4 9	4 4	4 0	3 8	
			0 . 5 6	1 . 0	6 9	5 9	5 3	4 8	6 7	5 9	5 3	4 8	6 5	5 7	5 2	4 8	6 2	5 6	5 1	4 7	4 5	
				1 . 2 5	7 4	6 6	6 0	5 5	7 3	6 5	6 0	5 5	7 0	6 4	5 9	5 5	6 8	6 2	5 8	5 4	5 2	
下方投影面積		cm ²		1 . 5	7 8	7 1	6 5	6 1	7 7	7 0	6 5	6 0	7 4	6 8	6 4	6 0	7 1	6 7	6 3	5 9	5 7	
等価発光面積		cm ²		2 . 0	8 3	7 7	7 2	6 8	8 2	7 6	7 2	6 8	7 9	7 4	7 1	6 7	7 7	7 3	6 9	6 7	6 4	
取付 高さ	器具間隔最大限			2 . 5	8 6	8 1	7 7	7 3	8 5	8 0	7 6	7 3	8 2	7 8	7 5	7 2	8 0	7 7	7 4	7 1	6 9	
	横方向 (A) 縦方向 (B)			3 . 0	8 8	8 4	8 0	7 7	8 7	8 3	7 9	7 7	8 4	8 1	7 8	7 5	8 2	7 9	7 7	7 4	7 2	
H m	1 . 2 8 H m	1 . 2 8 H m		4 . 0	9 1	8 7	8 4	8 2	8 9	8 6	8 4	8 1	8 7	8 4	8 2	8 0	8 5	8 2	8 1	7 9	7 6	
				5 . 0	9 2	8 9	8 7	8 5	9 1	8 8	8 6	8 4	8 8	8 6	8 4	8 3	8 6	8 4	8 3	8 1	7 9	
				7 . 0	9 4	9 2	9 0	8 8	9 3	9 1	8 9	8 7	9 0	8 9	8 7	8 6	8 8	8 7	8 6	8 4	8 2	
				1 0 . 0	9 5	9 4	9 2	9 1	9 4	9 3	9 1	9 0	9 2	9 0	8 9	8 8	8 9	8 9	8 8	8 7	8 4	

