

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 4
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184484 (0) DR 1
B Z 分類	BZ4 / 1.4 / BZ3

器具効率		73 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	43	35	29	25	42	34	29	25	41	34	29	25	39	33	28	25	24
			0.63	0.8	51	43	38	34	50	43	38	34	48	42	37	34	47	41	37	34	32
			0.56	1.0	56	49	44	40	55	49	44	40	53	47	43	40	51	46	43	40	38
				1.25	61	55	50	46	60	54	49	46	58	53	49	46	56	52	48	45	44
下方投影面積 等価発光面積		c m ² c m ²		1.5	64	58	54	50	63	58	53	50	61	56	53	50	59	55	52	49	48
				2.0	68	63	60	56	67	62	59	56	65	61	58	56	63	60	57	55	53
				2.5	70	66	63	60	69	66	63	60	67	64	62	59	65	63	61	59	57
				3.0	72	68	66	63	71	68	65	63	69	66	64	62	67	65	63	61	59
H m	1.30 H m	1.30 H m		4.0	74	71	69	67	73	70	68	66	71	69	67	65	69	67	66	64	63
				5.0	75	73	71	69	74	72	70	69	72	70	69	67	70	69	68	66	65
				7.0	76	75	73	72	75	74	72	71	73	72	71	70	72	71	70	69	67
				10.0	77	76	75	74	76	75	74	73	74	74	73	72	73	72	71	71	69

