

屋内照明器具特性	
品番 (品名)	LGB16124
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184485 (0) DR 1
BZ分類	BZ1

器具効率		88 %	反射率	天井	80 %				70 %				50 %				30 %				0 %						
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %						
				床	10 %				10 %				10 %				10 %				0 %						
上方光束		0 %	室指数	照明率 (X0.01)																				Z	C		M
下方光束		88 %																									
保守率		良 中 否	0.67	0.6	67	61	56	53	67	60	56	53	65	60	56	53	64	59	56	53	52						
			0.63	0.8	74	68	64	61	73	68	64	61	72	67	63	61	70	66	63	60	59						
			0.56	1.0	78	73	69	66	77	72	69	66	76	71	68	66	74	70	68	65	64						
			1.25	82	77	73	71	81	76	73	70	79	75	72	70	77	74	72	70	68							
下方投影面積		c m ²	1.5	84	80	77	74	83	79	76	74	81	78	75	73	79	77	74	73	71							
			2.0	87	83	81	78	86	83	80	78	84	81	79	77	82	80	78	77	75							
取付高さ	器具間隔最大限		2.5	89	86	83	81	88	85	83	81	86	83	82	80	84	82	80	79	77							
	横方向 (A)	縦方向 (B)	3.0	90	87	85	83	89	86	84	83	87	85	83	82	85	83	82	81	79							
H m	0.73 H m	0.73 H m	4.0	91	89	87	86	90	88	87	85	88	87	85	84	86	85	84	83	81							
			5.0	92	90	89	88	91	89	88	87	89	88	87	86	87	86	85	84	82							
			7.0	93	92	91	90	92	91	90	89	90	89	88	87	88	87	87	86	84							
			10.0	94	93	92	91	93	92	91	90	91	90	89	89	89	88	88	87	85							

