

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 4
光源	LLD5000LCC1 ×1 1140.0 l m
管理番号	K0190440 (0) DR 1
B Z 分類	B Z 3

器具効率		97 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	62	52	46	41	61	51	45	41	59	51	45	41	57	50	44	41	39				
			0.63	0.8	72	63	56	52	71	62	56	52	68	61	56	52	66	60	55	51	50				
			0.56	1.0	78	70	64	59	77	69	63	59	74	68	63	59	72	66	62	59	57				
				1.25	83	76	70	66	82	75	70	66	79	74	69	65	77	72	68	65	63				
下方投影面積		c m ²		1.5	87	80	75	71	85	79	74	71	83	78	73	70	80	76	72	69	67				
			等価発光面積	c m ²	2.0	91	86	81	78	90	85	81	77	87	83	79	76	85	81	78	76	74			
取付 高さ	器具間隔最大限			2.5	94	89	85	82	92	88	85	82	90	86	83	81	88	85	82	80	77				
	横方向 (A) 縦方向 (B)			3.0	95	92	88	85	94	91	87	85	92	89	86	84	89	87	85	83	80				
H m	1.26 H m 1.26 H m			4.0	98	95	92	89	96	94	91	89	94	92	89	88	92	90	88	86	84				
				5.0	99	97	94	92	98	96	93	91	95	93	92	90	93	92	90	89	86				
				7.0	101	99	97	95	99	98	96	95	97	96	94	93	95	94	93	91	89				
				10.0	102	100	99	98	101	99	98	97	98	97	96	95	96	95	94	94	91				

