

屋内照明器具特性	
品番 (品名)	LGB10825
光源	LLD3020LCE1 ×1 795.0 l m
管理番号	K0176304 (0) DR 1
B Z 分類	BZ1

器具効率		79 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		79 %																				
保守率		良	0.6	67	63	60	58	67	62	60	58	66	62	59	58	65	61	59	57	57		
		中	0.8	72	68	65	63	71	68	65	63	70	67	65	63	69	66	64	63	62		
		否	1.0	75	71	69	67	74	71	68	67	73	70	68	66	72	69	67	66	65		
			0.56	1.25	77	74	72	70	76	73	71	69	75	73	71	69	74	72	70	69	68	
下方投影面積		c m ²	1.5	78	76	74	72	78	75	73	72	76	74	72	71	75	73	72	71	69		
等価発光面積		c m ²	2.0	80	78	76	75	80	77	76	74	78	76	75	74	77	75	74	73	72		
取付 高さ	器具間隔最大限		2.5	81	80	78	77	81	79	77	76	79	78	76	75	78	76	75	75	73		
	横方向 (A)	縦方向 (B)	3.0	82	81	79	78	81	80	79	77	80	79	77	76	78	77	76	76	74		
H m	0.40 H m	0.40 H m	4.0	83	82	81	80	82	81	80	79	81	80	79	78	79	78	78	77	75		
			5.0	84	83	82	81	83	82	81	80	81	80	80	79	80	79	78	78	76		
			7.0	84	83	83	82	83	83	82	81	82	81	81	80	80	80	79	79	77		
			10.0	85	84	84	83	84	83	83	82	82	82	81	81	80	80	80	79	77		

