

屋内照明器具特性	
品番 (品名)	LGB10825
光源	LLD2020LCE1 ×1 460.0 lm
管理番号	K0176307 (0) DR1
BZ分類	BZ1

器具効率	8 7 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
			壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
			床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束	8 7 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束																				
保守率	良	0 . 6 7	0 . 6	7 4	6 9	6 6	6 3	7 3	6 9	6 6	6 3	7 2	6 8	6 5	6 3	7 1	6 8	6 5	6 3	6 2
	中	0 . 6 3	0 . 8	7 9	7 5	7 2	6 9	7 8	7 4	7 1	6 9	7 7	7 4	7 1	6 9	7 6	7 3	7 1	6 9	6 8
	否	0 . 5 6	1 . 0	8 2	7 8	7 5	7 3	8 1	7 8	7 5	7 3	8 0	7 7	7 5	7 3	7 9	7 6	7 4	7 2	7 1
		1 . 2 5	8 5	8 1	7 9	7 7	8 4	8 1	7 8	7 6	8 2	8 0	7 8	7 6	8 1	7 9	7 7	7 5	7 4	
下方投影面積	c m ²	1 . 5	8 6	8 3	8 1	7 9	8 5	8 3	8 0	7 9	8 4	8 1	8 0	7 8	8 2	8 0	7 9	7 7	7 6	
等価発光面積		c m ²	2 . 0	8 8	8 6	8 4	8 2	8 7	8 5	8 3	8 2	8 6	8 4	8 2	8 1	8 4	8 3	8 1	8 0	7 9
2 . 5		8 9	8 7	8 6	8 4	8 9	8 7	8 5	8 4	8 7	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 0		
取付 高さ	器具間隔最大限		3 . 0	9 0	8 8	8 7	8 5	8 9	8 8	8 6	8 5	8 8	8 6	8 5	8 4	8 6	8 5	8 4	8 3	8 1
	横方向 (A)	縦方向 (B)	4 . 0	9 1	9 0	8 9	8 7	9 0	8 9	8 8	8 7	8 8	8 7	8 6	8 6	8 7	8 6	8 5	8 4	8 3
H m	0 . 4 0 H m	0 . 4 0 H m	5 . 0	9 2	9 1	9 0	8 9	9 1	9 0	8 9	8 8	8 9	8 8	8 7	8 7	8 7	8 7	8 6	8 5	8 3
			7 . 0	9 2	9 2	9 1	9 0	9 1	9 1	9 0	8 9	9 0	8 9	8 8	8 8	8 8	8 7	8 7	8 6	8 4
			1 0 . 0	9 3	9 2	9 2	9 1	9 2	9 1	9 1	9 0	9 0	9 0	8 9	8 9	8 8	8 8	8 8	8 7	8 5

