

屋内照明器具特性	
品番 (品名)	LGB10825
光源	LLD3020MLCE1 ×1 795.0 lm
管理番号	K0176305 (0) DR1
BZ分類	BZ1

器具効率		77 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		0 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		77 %																							
保守率		良 中 否	0.67	0.6	65	61	58	56	65	60	58	56	64	60	58	56	63	60	57	56	55				
			0.63	0.8	70	66	63	61	69	65	63	61	68	65	63	61	67	64	62	61	60				
			0.56	1.0	72	69	66	65	72	69	66	64	71	68	66	64	69	67	65	64	63				
				1.25	75	72	69	67	74	71	69	67	73	70	68	67	71	69	68	66	65				
下方投影面積		c m ²		1.5	76	73	71	70	75	73	71	69	74	72	70	69	73	71	69	68	67				
等価発光面積			c m ²	2.0	78	76	74	72	77	75	73	72	76	74	73	71	74	73	72	71	69				
取付 高さ	器具間隔最大限		2.5	79	77	75	74	78	76	75	74	77	75	74	73	75	74	73	72	71					
	横方向 (A)		縦方向 (B)	3.0	80	78	77	75	79	77	76	75	77	76	75	74	76	75	74	73	72				
H m	0.40 H m		0.40 H m	4.0	80	79	78	77	80	78	77	77	78	77	76	75	77	76	75	74	73				
				5.0	81	80	79	78	80	79	78	78	78	78	77	76	77	76	76	75	73				
				7.0	82	81	80	79	81	80	79	79	79	78	78	77	77	77	77	76	74				
				10.0	82	81	81	80	81	81	80	80	79	79	79	78	78	78	77	77	75				

