

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 5
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184486 (0) DR 1
B Z 分類	BZ2 / 0.9 / BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		45 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		0 % 45 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.67	0.6	31	27	25	23	31	27	25	23	30	27	24	23	29	26	24	23	22
			0.63	0.8	36	32	30	28	35	32	30	28	35	32	29	28	34	31	29	28	27
			0.56	1.0	39	36	33	31	38	35	33	31	37	35	33	31	36	34	32	31	30
				1.25	41	38	36	34	40	38	36	34	39	37	35	34	38	37	35	34	33
下方投影面積 等価発光面積		c m ² c m ²		1.5	42	40	38	36	42	39	38	36	41	39	37	36	40	38	37	36	35
				2.0	44	42	40	39	43	42	40	39	42	41	40	38	41	40	39	38	37
取付 高さ	器具間隔最大限			2.5	45	43	42	41	44	43	42	41	43	42	41	40	42	41	40	40	39
	横方向 (A) 縦方向 (B)			3.0	46	44	43	42	45	44	43	42	44	43	42	41	43	42	41	41	40
H m	1.26 H m 1.26 H m			4.0	47	45	44	44	46	45	44	43	45	44	43	43	44	43	43	42	41
				5.0	47	46	45	45	46	46	45	44	45	45	44	44	44	44	43	43	42
				7.0	48	47	46	46	47	46	46	45	46	45	45	45	45	45	44	44	43
				10.0	48	48	47	47	47	47	47	46	46	46	46	45	45	45	45	45	43

