

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 5
光源	L L D 4 0 0 0 L C B 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 0 0 (0) D R 1
B Z 分類	B Z 2

器具効率		47 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																	Z	C	M
下方光束		47 %																					
保守率		良 中 否	0.67	0.6	31	26	23	21	31	26	23	21	30	26	23	21	29	25	23	21	20		
			0.63	0.8	36	32	29	27	35	32	29	27	34	31	29	27	33	30	28	27	26		
			0.56	1.0	39	35	33	31	38	35	32	31	37	34	32	30	36	34	32	30	29		
				1.25	41	38	36	34	41	38	35	34	40	37	35	33	39	36	35	33	32		
下方投影面積		cm ²	1.5	43	40	38	36	42	40	37	36	41	39	37	36	40	38	37	35	34			
等価発光面積		cm ²	2.0	45	42	41	39	44	42	40	39	43	41	40	38	42	40	39	38	37			
取付 高さ	器具間隔最大限		2.5	46	44	42	41	45	43	42	41	44	43	41	40	43	42	41	40	39			
	横方向 (A)	縦方向 (B)	3.0	47	45	44	42	46	44	43	42	45	44	42	41	44	43	42	41	40			
H m	1.28 H m	1.28 H m	4.0	48	46	45	44	47	46	45	44	46	45	44	43	45	44	43	43	41			
			5.0	48	47	46	45	48	47	46	45	46	46	45	44	45	45	44	44	42			
			7.0	49	48	47	47	48	48	47	46	47	47	46	45	46	46	45	45	43			
			10.0	49	49	48	48	49	48	48	47	48	47	47	46	47	46	46	46	44			

