

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 8
光源	L L D 4 0 0 0 L C T 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 9 0 5 1 1 (0) D R 1
B Z 分類	B Z 2

器具効率		49 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %				10 %				10 %				10 %				0 %
						室指数	照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 67	0 . 6	32	27	24	22	32	27	24	22	31	27	24	22	30	26	24	22	21	
			0 . 63	0 . 8	37	33	30	28	37	33	30	28	36	32	30	28	35	32	29	28	27	
			1 . 0	1 . 0	40	37	34	32	40	36	34	32	39	36	33	32	38	35	33	31	31	
			0 . 56	1 . 25	43	39	37	35	42	39	37	35	41	38	36	35	40	38	36	35	34	
下方投影面積		c m ²	1 . 5	44	41	39	37	44	41	39	37	43	40	38	37	41	40	38	37	36		
			2 . 0	46	44	42	40	46	44	42	40	45	43	41	40	43	42	41	39	38		
等価発光面積		c m ²	2 . 5	48	46	44	42	47	45	44	42	46	44	43	42	45	43	42	41	40		
			3 . 0	48	47	45	44	48	46	45	44	47	45	44	43	45	44	43	42	41		
H m	1 . 28 H m		1 . 28 H m	4 . 0	49	48	47	46	49	48	46	45	48	47	46	45	46	46	45	44		
				5 . 0	50	49	48	47	49	48	47	47	48	47	47	46	47	46	46	45		
				7 . 0	51	50	49	48	50	49	49	48	49	48	48	47	48	47	47	46		
				10 . 0	51	51	50	49	51	50	50	49	49	49	49	48	48	48	48	47		

