

屋内照明器具特性	
品番 (品名)	LGB10829
光源	LLD3020MLCB1 ×1 715.0 lm
管理番号	K0176306 (0) DR1
BZ分類	BZ1

器具効率		7 4 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		7 4 %																					
保守率		良	0 . 6 7	0 . 6	6 3	5 9	5 6	5 4	6 2	5 8	5 6	5 4	6 1	5 8	5 6	5 4	6 1	5 7	5 5	5 4	5 3		
		中	0 . 6 3	0 . 8	6 7	6 4	6 1	5 9	6 7	6 3	6 1	5 9	6 6	6 3	6 0	5 9	6 5	6 2	6 0	5 9	5 8		
		否	0 . 5 6	1 . 0	7 0	6 7	6 4	6 2	6 9	6 6	6 4	6 2	6 8	6 5	6 3	6 2	6 7	6 5	6 3	6 2	6 1		
				1 . 2 5	7 2	6 9	6 7	6 5	7 1	6 9	6 7	6 5	7 0	6 8	6 6	6 5	6 9	6 7	6 5	6 4	6 3		
下方投影面積		c m ²	1 . 5	7 3	7 1	6 9	6 7	7 3	7 0	6 8	6 7	7 1	6 9	6 8	6 6	7 0	6 9	6 7	6 6	6 5			
等価発光面積			c m ²	2 . 0	7 5	7 3	7 1	7 0	7 4	7 2	7 1	7 0	7 3	7 1	7 0	6 9	7 2	7 0	6 9	6 8	6 7		
取付 高さ	器具間隔最大限		2 . 5	7 6	7 4	7 3	7 2	7 5	7 4	7 2	7 1	7 4	7 3	7 1	7 0	7 3	7 2	7 1	7 0	6 8			
	横方向 (A)		縦方向 (B)	3 . 0	7 7	7 5	7 4	7 3	7 6	7 5	7 3	7 2	7 5	7 3	7 2	7 2	7 3	7 2	7 1	7 1	6 9		
H m	0 . 4 0 H m		0 . 4 0 H m	4 . 0	7 8	7 6	7 5	7 4	7 7	7 6	7 5	7 4	7 5	7 4	7 4	7 3	7 4	7 3	7 3	7 2	7 0		
				5 . 0	7 8	7 7	7 6	7 5	7 7	7 6	7 6	7 5	7 6	7 5	7 4	7 4	7 4	7 4	7 3	7 3	7 1		
				7 . 0	7 9	7 8	7 7	7 7	7 8	7 7	7 7	7 6	7 6	7 6	7 5	7 5	7 5	7 4	7 4	7 4	7 2		
				1 0 . 0	7 9	7 9	7 8	7 8	7 8	7 8	7 7	7 7	7 7	7 6	7 6	7 6	7 5	7 5	7 5	7 4	7 2		

