

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 9
光源	LLD40402CQ1 (KAKUSAN) ×1 860.0 l m
管理番号	K0184486 (0) DR 1
B Z 分類	BZ2 / 0.9 / BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		45 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		45 %																				
保守率		良 中 否	0.67	0.6	31	27	25	23	31	27	25	23	30	27	24	23	29	26	24	23	22	
			0.63	0.8	36	32	30	28	35	32	30	28	35	32	29	28	34	31	29	28	27	
			0.56	1.0	39	36	33	31	38	35	33	31	37	35	33	31	36	34	32	31	30	
				1.25	41	38	36	34	40	38	36	34	39	37	35	34	38	37	35	34	33	
下方投影面積		cm ²	1.5	42	40	38	36	42	39	38	36	41	39	37	36	40	38	37	36	35		
等価発光面積		cm ²	2.0	44	42	40	39	43	42	40	39	42	41	40	38	41	40	39	38	37		
取付 高さ	器具間隔最大限		2.5	45	43	42	41	44	43	42	41	43	42	41	40	42	41	40	40	39		
	横方向 (A)		縦方向 (B)		3.0	46	44	43	42	45	44	43	42	44	43	42	41	43	42	41	40	
H m	1.26 H m	1.26 H m	4.0	47	45	44	44	46	45	44	43	45	44	43	43	44	43	43	42	41		
			5.0	47	46	45	45	46	46	45	44	45	45	44	44	44	44	43	43	42		
			7.0	48	47	46	46	47	46	46	45	46	45	45	45	45	45	44	44	43		
			10.0	48	48	47	47	47	47	47	46	46	46	46	45	45	45	45	45	43		

