

屋内照明器具特性	
品番 (品名)	LGB10829
光源	LLD40402CQ1 (SHUKOU) ×1 620.0 l m
管理番号	K0184487 (0) DR 1
BZ分類	BZ1

器具効率		8 2 %	反 射 率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
上方光束		0 %	室指数	床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
下方光束		8 2 %		照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 7	0 . 6	6 5	5 9	5 5	5 3	6 4	5 9	5 5	5 3	6 3	5 8	5 5	5 3	6 2	5 8	5 5	5 3	5 2
			0 . 6 3	0 . 8	7 1	6 6	6 3	6 0	7 1	6 6	6 2	6 0	6 9	6 5	6 2	6 0	6 8	6 4	6 2	6 0	5 9
			0 . 5 6	1 . 0	7 5	7 0	6 7	6 5	7 4	7 0	6 7	6 5	7 3	6 9	6 6	6 4	7 1	6 8	6 6	6 4	6 3
			1 . 2 5	7 8	7 4	7 1	6 9	7 7	7 3	7 1	6 8	7 6	7 2	7 0	6 8	7 4	7 1	6 9	6 8	6 6	
下方投影面積		c m ²	1 . 5	8 0	7 6	7 4	7 1	7 9	7 6	7 3	7 1	7 7	7 5	7 2	7 1	7 6	7 4	7 2	7 0	6 9	
			等価発光面積	c m ²	2 . 0	8 2	7 9	7 7	7 5	8 1	7 9	7 7	7 5	8 0	7 8	7 6	7 4	7 8	7 6	7 5	7 3
取付 高さ	器具間隔最大限		2 . 5	8 4	8 1	7 9	7 8	8 3	8 1	7 9	7 7	8 1	7 9	7 8	7 6	7 9	7 8	7 7	7 6	7 4	
	横方向 (A) 縦方向 (B)		3 . 0	8 5	8 3	8 1	7 9	8 4	8 2	8 0	7 9	8 2	8 0	7 9	7 8	8 0	7 9	7 8	7 7	7 5	
H m	0 . 7 5 H m	0 . 7 5 H m	4 . 0	8 6	8 4	8 3	8 1	8 5	8 3	8 2	8 1	8 3	8 2	8 1	8 0	8 1	8 0	8 0	7 9	7 7	
			5 . 0	8 6	8 5	8 4	8 3	8 5	8 4	8 3	8 2	8 4	8 3	8 2	8 1	8 2	8 1	8 1	8 0	7 8	
			7 . 0	8 7	8 6	8 5	8 5	8 6	8 5	8 5	8 4	8 4	8 4	8 3	8 2	8 3	8 2	8 2	8 1	7 9	
			1 0 . 0	8 8	8 7	8 6	8 6	8 7	8 6	8 6	8 5	8 5	8 4	8 4	8 4	8 3	8 3	8 2	8 2	8 0	

