

| 屋内照明器具特性 |                           |
|----------|---------------------------|
| 品番 (品名)  | LGB10829                  |
| 光源       | LLD5010LCC1 ×1 1095.0 l m |
| 管理番号     | K0190432 ( 0 ) DR 1       |
| B Z 分類   | BZ1                       |

| 器具効率     |           | 93 %             | 反<br>射<br>率 | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |   |   |   |
|----------|-----------|------------------|-------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|---|---|---|
|          |           |                  |             | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |   |   |   |
|          |           |                  |             | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |   |   |   |
| 上方光束     |           | 0 %              | 室指数         | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     | Z | C | M |
| 下方光束     |           | 93 %             |             |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |   |   |   |
| 保守率      |           | 良                | 0.67        | 0.6           | 80   | 75 | 71 | 69 | 79   | 74 | 71 | 69 | 78   | 74 | 71 | 69 | 77   | 73 | 71 | 69 | 68  |   |   |   |
|          |           | 中                | 0.63        | 0.8           | 85   | 80 | 77 | 75 | 84   | 80 | 77 | 74 | 83   | 79 | 76 | 74 | 82   | 78 | 76 | 74 | 73  |   |   |   |
|          |           | 否                | 0.56        | 1.0           | 88   | 84 | 81 | 78 | 87   | 83 | 80 | 78 | 86   | 82 | 80 | 78 | 84   | 82 | 79 | 78 | 76  |   |   |   |
|          |           |                  |             | 1.25          | 91   | 87 | 84 | 82 | 90   | 86 | 84 | 82 | 88   | 85 | 83 | 81 | 87   | 84 | 82 | 81 | 79  |   |   |   |
| 下方投影面積   |           | c m <sup>2</sup> |             | 1.5           | 92   | 89 | 86 | 84 | 91   | 88 | 86 | 84 | 90   | 87 | 85 | 83 | 88   | 86 | 84 | 83 | 81  |   |   |   |
| 等価発光面積   |           | c m <sup>2</sup> |             | 2.0           | 94   | 92 | 90 | 88 | 94   | 91 | 89 | 87 | 92   | 90 | 88 | 87 | 90   | 88 | 87 | 86 | 84  |   |   |   |
| 取付<br>高さ | 器具間隔最大限   |                  |             | 2.5           | 96   | 94 | 92 | 90 | 95   | 93 | 91 | 89 | 93   | 91 | 90 | 89 | 91   | 90 | 89 | 88 | 86  |   |   |   |
|          | 横方向 ( A ) |                  | 縦方向 ( B )   | 3.0           | 97   | 95 | 93 | 92 | 96   | 94 | 92 | 91 | 94   | 92 | 91 | 90 | 92   | 91 | 90 | 89 | 87  |   |   |   |
| H m      | 0.81 H m  |                  | 0.81 H m    | 4.0           | 98   | 96 | 95 | 94 | 97   | 95 | 94 | 93 | 95   | 94 | 93 | 92 | 93   | 92 | 91 | 91 | 88  |   |   |   |
|          |           |                  |             | 5.0           | 98   | 97 | 96 | 95 | 97   | 96 | 95 | 94 | 95   | 95 | 94 | 93 | 94   | 93 | 92 | 92 | 89  |   |   |   |
|          |           |                  |             | 7.0           | 99   | 98 | 97 | 97 | 98   | 97 | 97 | 96 | 96   | 95 | 95 | 94 | 94   | 94 | 93 | 93 | 90  |   |   |   |
|          |           |                  |             | 10.0          | 100  | 99 | 99 | 98 | 99   | 98 | 98 | 97 | 97   | 96 | 96 | 95 | 95   | 94 | 94 | 94 | 91  |   |   |   |

