

屋内照明器具特性	
品番 (品名)	LGB10829
光源	LLD5020LCC1 ×1 1085.0 l m
管理番号	K0190433 (0) DR 1
B Z 分類	BZ1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
上方光束		1 %	室指数	照明率 (X0.01)																			
下方光束		82 %		Z C M																			
保守率		良	0.67	0.6	66	61	57	55	66	60	57	54	64	60	57	54	63	59	56	54	53		
		中	0.63	0.8	72	67	63	61	71	66	63	61	70	66	63	60	68	65	62	60	59		
		否	0.56	1.0	75	71	67	65	74	70	67	65	73	69	67	64	72	68	66	64	63		
				1.25	78	74	71	69	77	73	71	68	76	72	70	68	74	71	69	68	66		
下方投影面積		c m ²		1.5	80	76	74	71	79	76	73	71	77	75	72	71	76	74	72	70	69		
等価発光面積		c m ²		2.0	82	80	77	75	81	79	77	75	80	78	76	74	78	76	75	74	72		
取付高さ	器具間隔最大限			2.5	84	81	79	78	83	81	79	77	81	79	78	76	80	78	77	76	74		
	横方向 (A)		縦方向 (B)	3.0	85	83	81	79	84	82	80	79	82	81	79	78	81	79	78	77	75		
H m	0.43 H m		0.43 H m	4.0	86	84	83	82	85	84	82	81	83	82	81	80	82	81	80	79	77		
				5.0	87	85	84	83	86	85	84	83	84	83	82	81	82	82	81	80	78		
				7.0	88	87	86	85	87	86	85	84	85	84	83	83	83	83	82	82	79		
				10.0	88	87	87	86	87	87	86	86	85	85	84	84	84	83	83	83	80		

