

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 2 9
光源	L L D 2 0 0 0 L C T 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 9 0 5 1 2 (0) D R 1
B Z 分類	B Z 2

器具効率		5 5 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	3 6	3 1	2 7	2 5	3 6	3 1	2 7	2 5	3 5	3 0	2 7	2 5	3 4	3 0	2 7	2 5	2 4
			0 . 6 3	0 . 8	4 2	3 7	3 4	3 2	4 1	3 7	3 4	3 2	4 0	3 6	3 3	3 1	3 9	3 6	3 3	3 1	3 0
			0 . 5 6	1 . 0	4 5	4 1	3 8	3 6	4 5	4 1	3 8	3 6	4 4	4 0	3 8	3 6	4 2	3 9	3 7	3 5	3 4
				1 . 2 5	4 8	4 5	4 2	4 0	4 8	4 4	4 1	3 9	4 6	4 3	4 1	3 9	4 5	4 3	4 1	3 9	3 8
下方投影面積 等価発光面積		c m ² c m ²		1 . 5	5 0	4 7	4 4	4 2	4 9	4 6	4 4	4 2	4 8	4 5	4 3	4 2	4 7	4 5	4 3	4 1	4 0
				2 . 0	5 2	5 0	4 7	4 6	5 2	4 9	4 7	4 5	5 0	4 8	4 6	4 5	4 9	4 7	4 6	4 4	4 3
				2 . 5	5 4	5 1	4 9	4 8	5 3	5 1	4 9	4 8	5 2	5 0	4 8	4 7	5 0	4 9	4 8	4 6	4 5
取付 高さ	器具間隔最大限			3 . 0	5 5	5 3	5 1	4 9	5 4	5 2	5 0	4 9	5 2	5 1	5 0	4 8	5 1	5 0	4 9	4 8	4 7
	横方向 (A)	縦方向 (B)		4 . 0	5 6	5 4	5 3	5 2	5 5	5 4	5 2	5 1	5 4	5 2	5 1	5 0	5 2	5 1	5 1	5 0	4 8
H m	1 . 2 8 H m	1 . 2 8 H m		5 . 0	5 6	5 5	5 4	5 3	5 6	5 4	5 3	5 2	5 4	5 3	5 2	5 2	5 3	5 2	5 2	5 1	4 9
				7 . 0	5 7	5 6	5 5	5 5	5 6	5 6	5 5	5 4	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 2	5 1
				1 0 . 0	5 8	5 7	5 6	5 6	5 7	5 6	5 6	5 5	5 6	5 5	5 5	5 4	5 4	5 4	5 4	5 3	5 2

