

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 2 9
光源	LLD2000LCE1 ×1 531.0 lm
管理番号	K0176303 (0) DR 1
B Z 分類	B Z 2

器具効率		62 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 62 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	41	35	31	29	41	35	31	29	39	34	31	28	38	34	31	28	27	
			0.63	0.8	48	42	39	36	47	42	39	36	46	41	38	36	45	41	38	36	35	
			1.0	52	47	44	41	51	47	43	41	50	46	43	41	48	45	42	40	39		
			0.56	1.25	55	51	48	45	54	50	47	45	53	49	47	45	51	48	46	44	43	
下方投影面積 等価発光面積		cm ² cm ²	1.5	57	53	50	48	56	53	50	48	55	52	49	47	53	51	49	47	46		
			2.0	60	56	54	52	59	56	54	52	57	55	53	51	56	54	52	51	49		
取付 高さ	器具間隔最大限		2.5	61	59	56	55	60	58	56	54	59	57	55	54	57	56	54	53	52		
	横方向 (A) 縦方向 (B)		3.0	62	60	58	56	61	59	58	56	60	58	57	55	58	57	56	55	53		
H m	1.28 H m 1.28 H m		4.0	63	62	60	59	63	61	60	58	61	60	59	58	60	59	58	57	55		
			5.0	64	63	61	60	63	62	61	60	62	61	60	59	60	60	59	58	56		
			7.0	65	64	63	62	64	63	62	62	63	62	61	61	61	61	60	60	58		
			10.0	66	65	64	64	65	64	64	63	63	63	62	62	62	62	61	61	59		

