

屋内照明器具特性	
品番 (品名)	XLGB1003
光源	LLD2000VCE1 ×1 531.0 lm
管理番号	K0176283 (0) DR 1
BZ分類	BZ5/0.7/BZ4/6.0/BZ3

器具効率		8 7 % 上方光束 1 % 下方光束 8 6 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 1	4 0	3 4	2 9	4 9	4 0	3 4	2 9	4 7	3 9	3 3	2 9	4 6	3 8	3 3	2 9	2 7	
			0 . 6 3	0 . 8	6 0	5 0	4 4	3 9	5 8	5 0	4 3	3 9	5 6	4 8	4 3	3 9	5 4	4 7	4 2	3 8	3 7	
			0 . 5 6	1 . 0	6 6	5 7	5 1	4 6	6 4	5 6	5 0	4 6	6 2	5 5	5 0	4 6	6 0	5 4	4 9	4 5	4 3	
			1 . 2 5	7 1	6 3	5 8	5 3	7 0	6 3	5 7	5 3	6 7	6 1	5 6	5 2	6 5	6 0	5 5	5 2	5 0		
下方投影面積 等価発光面積		c m ²	1 . 5	7 5	6 8	6 2	5 8	7 3	6 7	6 2	5 8	7 1	6 5	6 1	5 7	6 8	6 4	6 0	5 7	5 5		
			2 . 0	7 9	7 4	6 9	6 6	7 8	7 3	6 9	6 5	7 6	7 1	6 8	6 4	7 3	7 0	6 6	6 4	6 2		
取付 高さ	器具間隔最大限			2 . 5	8 2	7 8	7 4	7 0	8 1	7 7	7 3	7 0	7 9	7 5	7 2	6 9	7 6	7 3	7 1	6 8	6 6	
	横方向 (A)		縦方向 (B)	3 . 0	8 4	8 0	7 7	7 4	8 3	7 9	7 6	7 3	8 1	7 8	7 5	7 2	7 8	7 6	7 3	7 1	6 9	
H m	1 . 2 8 H m		1 . 2 8 H m	4 . 0	8 7	8 4	8 1	7 8	8 6	8 3	8 0	7 8	8 3	8 1	7 9	7 7	8 1	7 9	7 7	7 5	7 3	
				5 . 0	8 8	8 6	8 3	8 1	8 7	8 5	8 2	8 1	8 5	8 3	8 1	7 9	8 3	8 1	7 9	7 8	7 6	
				7 . 0	9 0	8 8	8 6	8 5	8 9	8 7	8 5	8 4	8 6	8 5	8 4	8 2	8 4	8 3	8 2	8 1	7 8	
				1 0 . 0	9 1	9 0	8 8	8 7	9 0	8 9	8 7	8 6	8 8	8 7	8 6	8 5	8 6	8 5	8 4	8 3	8 1	

