

屋内照明器具特性	
品番 (品名)	XLGB1130
光源	LLD20001CQ1 ×1 531.0 lm
管理番号	K0176313 (0) DR1
BZ分類	BZ3

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		
下方光束		85 %		Z CM																		
保守率		良 中 否	0.67	0.6	56	47	41	38	55	47	41	38	53	46	41	37	51	45	41	37	36	
			0.63	0.8	64	56	50	47	63	55	50	46	61	54	50	46	59	53	49	46	45	
			1.0	69	62	57	53	68	61	56	53	66	60	56	52	64	59	55	52	50		
			0.56	1.25	73	67	62	58	72	66	62	58	70	65	61	58	68	63	60	57	56	
下方投影面積		cm ²	1.5	76	70	66	62	75	69	65	62	73	68	64	61	71	67	64	61	59		
等価発光面積		cm ²	2.0	80	75	71	68	79	74	71	68	76	73	70	67	74	71	69	66	64		
取付 高さ	器具間隔最大限		2.5	82	78	75	72	81	77	74	71	79	76	73	71	77	74	72	70	68		
	横方向 (A)	縦方向 (B)	3.0	84	80	77	75	82	79	77	74	80	78	75	73	78	76	74	72	70		
H m	1.39 H m	1.39 H m	4.0	86	83	80	78	84	82	80	78	82	80	78	77	80	79	77	75	73		
			5.0	87	85	83	81	86	84	82	80	84	82	80	79	82	80	79	78	75		
			7.0	88	87	85	84	87	86	84	83	85	84	83	81	83	82	81	80	78		
			10.0	89	88	87	86	88	87	86	85	86	85	84	83	84	83	83	82	80		

