

屋内照明器具特性	
品番 (品名)	LGBZ8212K
光源	LED6200_70_4150 ×1 4150.0 lm
管理番号	K0163269 (1) DB 1
BZ分類	BZ6 / 0.7 / BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		17 % 83 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	52	40	32	27	50	39	31	26	46	36	30	25	42	34	28	24	21	
			0.6	0.8	62	50	42	36	59	48	41	35	55	45	39	34	50	43	37	32	29	
			0.56	1.0	68	57	49	43	65	55	48	42	60	52	45	40	55	48	43	38	34	
				1.25	74	64	56	50	71	62	55	49	66	58	52	47	60	54	49	45	40	
下方投影面積		cm ²	1.5	78	69	61	56	75	67	60	54	69	62	56	52	64	58	53	49	44		
等価発光面積		cm ²	2.0	84	76	69	64	81	73	67	62	75	69	64	59	69	64	60	56	51		
取付 高さ	器具間隔最大限		2.5	87	80	75	70	84	78	73	68	78	73	68	65	73	68	65	61	55		
	横方向 (A) 縦方向 (B)		3.0	90	84	79	74	87	81	76	72	81	76	72	68	75	71	68	65	59		
1.5m	1.98 m	1.97 m	4.0	93	88	84	80	90	86	82	78	84	80	77	74	78	75	73	70	64		
2	2.6	2.6	5.0	95	91	87	84	92	88	85	82	86	83	80	78	80	78	76	73	67		
2.5	3.25	3.24	7.0	98	95	92	89	95	92	89	87	89	86	84	82	83	81	79	78	71		
3	3.9	3.89	10.0	100	97	95	93	97	95	93	91	91	89	87	86	85	84	82	81	74		

