

屋内照明器具特性	
品番 (品名)	LGBZ7217K
光源	LED6200_70_3900 ×1 3900.0 lm
管理番号	K0163277 (1) DB 1
BZ分類	BZ5

器具効率		100 % 上方光束 10 % 下方光束 90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
		90 %	室指数	照明率 (X0.01)																	ZCM	
保守率		良 中 否	0.63	0.6	55	43	35	30	53	42	35	29	50	40	33	29	47	38	32	28	25	
			0.6	0.8	64	53	45	39	62	52	44	39	58	49	43	38	55	47	41	37	34	
			0.56	1.0	71	60	52	46	69	59	51	46	64	56	49	44	60	53	48	43	40	
				1.25	77	67	59	53	74	65	58	53	70	62	56	51	66	59	54	50	46	
下方投影面積		cm ²		1.5	81	71	64	59	78	70	63	58	73	66	61	56	69	63	58	54	50	
等価発光面積			cm ²	2.0	86	78	72	67	84	76	71	66	79	73	68	64	74	69	65	61	57	
取付 高さ	器具間隔最大限			2.5	90	83	77	72	87	81	76	71	82	77	73	69	78	73	70	66	62	
	横方向 (A) 縦方向 (B)		3.0	92	86	81	77	90	84	79	75	85	80	76	73	80	76	73	70	65		
1.5m	1.84 m	1.86 m	4.0	95	90	86	82	93	88	84	81	88	84	81	78	84	81	78	75	70		
2	2.43	2.44	5.0	97	93	90	86	95	91	88	85	90	87	84	82	86	83	81	79	74		
2.5	3.03	3.05	7.0	100	97	94	91	97	94	92	89	93	90	88	86	88	86	84	83	77		
3	3.61	3.64	10.0	102	99	97	95	99	97	95	93	95	93	91	90	90	89	88	86	81		

