

屋内照明器具特性	
品番 (品名)	S P L 5 4 2 7
光源	L L D 5 0 0 0 L C C 1 × 4 1 1 4 0 . 0 l m
管理番号	K 0 1 9 0 3 9 6 (0) D R 1
B Z 分類	B Z 3

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		2 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		98 %																						
保守率		良 中 否	0 . 67	0 . 6	64	53	47	42	62	53	46	42	60	51	46	41	58	50	45	41	39			
			0 . 63	0 . 8	74	64	58	53	72	63	57	53	70	62	57	52	67	61	56	52	50			
			0 . 56	1 . 0	80	71	65	61	79	71	65	60	76	69	64	60	73	67	63	59	57			
				1 . 25	85	78	72	68	84	77	71	67	81	75	70	66	78	73	69	66	63			
下方投影面積		c m ²	1 . 5	89	82	77	72	87	81	76	72	84	79	75	71	82	77	73	70	68				
等価発光面積			c m ²	2 . 0	93	88	83	79	92	87	82	79	89	85	81	78	86	82	79	77	74			
取付 高さ	器具間隔最大限		2 . 5	96	92	87	84	95	90	87	83	92	88	85	82	89	86	83	81	78				
	横方向 (A)		縦方向 (B)		3 . 0	98	94	90	87	97	93	89	87	94	90	88	85	91	88	86	84	81		
H m	1 . 25 H m	1 . 25 H m	4 . 0	101	97	94	92	99	96	93	91	96	93	91	89	93	91	89	88	84				
			5 . 0	102	99	97	95	100	98	96	94	97	95	93	92	95	93	91	90	87				
			7 . 0	104	102	100	98	102	100	99	97	99	98	96	95	96	95	94	93	90				
			10 . 0	105	103	102	101	103	102	101	100	100	99	98	97	98	97	96	95	92				

