

屋内照明器具特性	
品番 (品名)	L G B 5 8 1 0 0
光源	L L D 2 0 0 0 L C E 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 6 3 8 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4

器具効率		9 0 %	反射率	天井	8 0 %					7 0 %					5 0 %					3 0 %					0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
					床	1 0 %					1 0 %					1 0 %					1 0 %					0 %
						室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 7	0 . 6	5 3	4 2	3 5	3 0	5 1	4 1	3 5	3 0	4 9	4 0	3 4	3 0	4 7	3 9	3 4	3 0	2 8					
			0 . 6 3	0 . 8	6 2	5 2	4 5	4 0	6 1	5 1	4 5	4 0	5 8	5 0	4 4	4 0	5 6	4 9	4 3	3 9	3 8					
			1 . 0	1 . 0	6 8	5 9	5 2	4 7	6 7	5 8	5 2	4 7	6 4	5 7	5 1	4 7	6 2	5 5	5 0	4 6	4 4					
			0 . 5 6	1 . 2 5	7 3	6 5	5 9	5 4	7 2	6 4	5 8	5 4	6 9	6 3	5 8	5 3	6 7	6 1	5 7	5 3	5 1					
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	7 7	7 0	6 4	5 9	7 6	6 9	6 3	5 9	7 3	6 7	6 2	5 8	7 1	6 5	6 1	5 8	5 6						
			2 . 0	8 2	7 6	7 1	6 7	8 1	7 5	7 0	6 6	7 8	7 3	6 9	6 6	7 6	7 1	6 8	6 5	6 3						
			2 . 5	8 5	8 0	7 6	7 2	8 4	7 9	7 5	7 1	8 1	7 7	7 4	7 0	7 9	7 5	7 2	7 0	6 7						
取付 高さ	器具間隔最大限		3 . 0	8 7	8 3	7 9	7 6	8 6	8 2	7 8	7 5	8 3	8 0	7 7	7 4	8 1	7 8	7 5	7 3	7 1						
	横方向 (A) 縦方向 (B)																									
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	9 0	8 6	8 3	8 0	8 9	8 5	8 2	8 0	8 6	8 3	8 1	7 9	8 4	8 2	7 9	7 8	7 5						
			5 . 0	9 2	8 9	8 6	8 4	9 0	8 8	8 5	8 3	8 8	8 6	8 4	8 2	8 6	8 4	8 2	8 0	7 8						
			7 . 0	9 3	9 1	8 9	8 7	9 2	9 0	8 8	8 7	9 0	8 8	8 7	8 5	8 8	8 6	8 5	8 4	8 1						
			1 0 . 0	9 5	9 3	9 2	9 0	9 4	9 2	9 1	8 9	9 1	9 0	8 9	8 8	8 9	8 8	8 7	8 6	8 4						

