

屋内照明器具特性	
品番 (品名)	L G B 5 8 1 0 0
光源	L L D 2 0 2 0 L C E 1 × 1 4 6 0 . 0 l m
管理番号	K 0 1 7 5 6 4 1 (0) D R 1
B Z 分類	B Z 1

器具効率	93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
			床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数	照明率 (X0.01) ZCM																		
下方光束	93 %																				
保守率	良 中 否	0.67	0.6	76	70	66	64	76	70	66	63	74	69	66	63	73	69	66	63	62	
		0.63	0.8	82	77	73	70	81	76	73	70	80	75	72	70	78	74	72	69	68	
		0.56	1.0	86	81	77	74	85	80	77	74	83	79	76	74	82	78	76	73	72	
			1.25	89	84	81	78	88	84	81	78	86	82	80	78	84	81	79	77	76	
下方投影面積	c m ²		1.5	91	87	84	81	90	86	83	81	88	85	82	80	86	84	82	80	78	
等価発光面積		c m ²	2.0	93	90	87	85	92	89	87	85	90	88	86	84	89	87	85	83	82	
		2.5	95	92	90	88	94	91	89	87	92	90	88	87	90	88	87	86	84		
取付高さ	器具間隔最大限		3.0	96	94	92	90	95	93	91	89	93	91	90	88	91	90	88	87	85	
H m	0.42 H m	0.42 H m	4.0	97	95	94	92	96	95	93	92	94	93	92	90	92	91	90	89	87	
			5.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	91	88	
			7.0	99	98	97	96	98	97	96	95	96	95	94	94	94	93	93	92	90	
			10.0	100	99	98	97	99	98	97	96	96	96	95	95	95	94	94	93	91	

