

屋内照明器具特性	
品番 (品名)	L G B 5 8 1 0 0
光源	L L D 2 0 0 0 1 C Q 1 × 1 5 3 1 . 0 l m
管理番号	K 0 1 7 5 6 4 3 (0) D R 1
B Z 分類	B Z 5 / 0 . 7 / B Z 4

器具効率		90 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		90 %		室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	53	42	35	30	52	42	35	30	50	41	35	30	48	40	34	30	28
			0 . 6 3	0 . 8	62	52	45	40	61	51	45	40	58	50	44	40	56	49	44	40	38
			1 . 0	68	59	52	47	67	58	52	47	64	57	51	47	62	56	51	47	45	
			0 . 5 6	1 . 2 5	74	65	59	54	72	65	59	54	70	63	58	54	67	62	57	53	51
下方投影面積		c m ²	1 . 5	77	70	64	60	76	69	64	59	73	67	63	59	71	66	62	58	56	
等価発光面積		c m ²	2 . 0	82	76	71	67	81	75	71	67	78	73	69	66	76	72	68	65	63	
取付 高さ	器具間隔最大限		2 . 5	85	80	76	72	84	79	75	72	81	77	74	71	79	76	73	70	68	
	横方向 (A)	縦方向 (B)	3 . 0	87	83	79	76	86	82	78	75	84	80	77	74	81	78	76	73	71	
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	90	87	83	81	89	86	83	80	86	84	81	79	84	82	80	78	75	
			5 . 0	92	89	86	84	90	88	85	83	88	86	84	82	86	84	82	80	78	
			7 . 0	93	91	89	87	92	90	88	87	90	88	87	85	88	86	85	84	81	
			10 . 0	95	93	92	90	94	92	91	90	91	90	89	88	89	88	87	86	84	

