

屋内照明器具特性	
品番 (品名)	L G B 5 8 1 0 0
光源	L L D 3 0 0 0 C U 1 × 1 7 9 5 . 0 l m
管理番号	K 0 1 7 9 1 1 4 (0) D R 1
B Z 分類	B Z 5 / 1 . 8 / B Z 4 / 6 . 0 / B Z 5 / 8 . 5 / B Z 4

器具効率		8 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束		1 %	室指数	照明率 (X 0 . 0 1)																			Z C M
下方光束		8 5 %																					
保守率		良 中 否	0 . 6 7	0 . 6	4 9	3 8	3 2	2 7	4 8	3 8	3 2	2 7	4 6	3 7	3 1	2 7	4 4	3 6	3 1	2 7	2 5		
			0 . 6 3	0 . 8	5 7	4 8	4 1	3 6	5 6	4 7	4 1	3 6	5 4	4 6	4 0	3 6	5 2	4 5	4 0	3 6	3 4		
			0 . 5 6	1 . 0	6 3	5 4	4 8	4 3	6 2	5 3	4 7	4 3	5 9	5 2	4 7	4 2	5 7	5 1	4 6	4 2	4 0		
				1 . 2 5	6 8	6 0	5 4	4 9	6 7	5 9	5 4	4 9	6 4	5 8	5 3	4 9	6 2	5 6	5 2	4 8	4 6		
下方投影面積		c m ²	1 . 5	7 2	6 4	5 9	5 4	7 0	6 4	5 8	5 4	6 8	6 2	5 7	5 3	6 5	6 0	5 6	5 3	5 1			
等価発光面積		c m ²	2 . 0	7 7	7 1	6 5	6 1	7 5	7 0	6 5	6 1	7 3	6 8	6 4	6 0	7 0	6 6	6 3	6 0	5 7			
取付 高さ	器具間隔最大限		2 . 5	8 0	7 4	7 0	6 6	7 8	7 3	6 9	6 6	7 6	7 2	6 8	6 5	7 3	7 0	6 7	6 4	6 2			
	横方向 (A)	縦方向 (B)	3 . 0	8 2	7 7	7 3	7 0	8 0	7 6	7 3	6 9	7 8	7 4	7 1	6 8	7 5	7 2	7 0	6 7	6 5			
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	8 4	8 1	7 8	7 5	8 3	8 0	7 7	7 4	8 1	7 8	7 5	7 3	7 8	7 6	7 4	7 2	7 0			
			5 . 0	8 6	8 3	8 0	7 8	8 5	8 2	8 0	7 7	8 2	8 0	7 8	7 6	8 0	7 8	7 6	7 5	7 2			
			7 . 0	8 8	8 6	8 4	8 2	8 7	8 5	8 3	8 1	8 4	8 3	8 1	7 9	8 2	8 1	7 9	7 8	7 6			
			1 0 . 0	8 9	8 8	8 6	8 5	8 8	8 7	8 5	8 4	8 6	8 5	8 3	8 2	8 4	8 3	8 2	8 1	7 8			

