

屋内照明器具特性	
品番 (品名)	XLGB3310
光源	LLD4000MNCE1 ×1 845.0 lm
管理番号	K0175637 (0) DR 1
BZ分類	BZ5 / 0.7 / BZ4

器具効率		86 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	50	40	33	29	49	39	33	29	47	38	33	29	45	38	32	28	27				
			0.63	0.8	59	49	43	38	58	49	43	38	56	48	42	38	53	47	42	38	36				
			0.56	1.0	65	56	50	45	64	55	49	45	61	54	49	44	59	53	48	44	42				
				1.25	70	62	56	52	69	61	56	51	66	60	55	51	64	58	54	51	49				
下方投影面積		cm ²		1.5	74	67	61	57	72	66	60	56	70	64	60	56	67	63	59	55	53				
			等価発光面積	cm ²	2.0	78	73	68	64	77	72	67	63	75	70	66	63	72	68	65	62	60			
取付高さ	器具間隔最大限			2.5	81	76	72	69	80	75	72	68	78	74	70	67	75	72	69	67	64				
	横方向 (A)	縦方向 (B)		3.0	83	79	75	72	82	78	75	72	80	76	73	71	77	75	72	70	68				
H m	1.27 H m	1.27 H m		4.0	86	83	80	77	85	82	79	76	82	80	77	75	80	78	76	74	72				
				5.0	87	85	82	80	86	84	81	79	84	82	80	78	82	80	78	77	74				
				7.0	89	87	85	83	88	86	84	83	86	84	83	81	84	82	81	80	78				
				10.0	90	89	88	86	89	88	87	86	87	86	85	84	85	84	83	82	80				

