

屋内照明器具特性	
品番 (品名)	XLGB3351
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0175644 (0) DR 1
BZ分類	BZ4

器具効率		75 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.67	0.6	44	35	30	26	43	35	29	26	41	34	29	26	40	33	29	26	24
			0.63	0.8	52	44	38	34	51	43	38	34	49	42	37	34	47	41	37	34	32
			0.56	1.0	57	49	44	40	56	49	44	40	54	48	43	40	52	47	43	39	38
				1.25	61	55	50	46	60	54	49	46	58	53	49	45	56	51	48	45	43
下方投影面積		cm ²		1.5	64	58	54	50	63	58	53	50	61	56	52	49	59	55	52	49	47
			等価発光面積	cm ²	2.0	68	63	60	56	67	63	59	56	65	61	58	55	63	60	57	55
取付 高さ	器具間隔最大限			2.5	71	67	63	60	70	66	63	60	68	64	62	59	66	63	61	59	57
	横方向 (A) 縦方向 (B)			3.0	72	69	66	63	71	68	65	63	69	67	64	62	67	65	63	61	59
H m	1.24 H m	1.24 H m		4.0	75	72	69	67	74	71	69	67	72	69	67	66	70	68	66	65	63
				5.0	76	74	72	70	75	73	71	69	73	71	70	68	71	70	68	67	65
				7.0	77	76	74	73	76	75	73	72	74	73	72	71	73	72	71	70	68
				10.0	78	77	76	75	77	76	75	74	75	75	74	73	74	73	72	72	69

