

屋内照明器具特性	
品番 (品名)	XLGB3020
光源	LLD2020NCE1 ×1 460.0 l m
管理番号	K0175641 (0) DR 1
B Z 分類	BZ1

器具効率		93 %	反 射 率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		0 %	室指数	照明率 (X0.01)																		Z C M
下方光束		93 %																				
保守率		良 中 否	0.67	0.6	76	70	66	64	76	70	66	63	74	69	66	63	73	69	66	63	62	
			0.63	0.8	82	77	73	70	81	76	73	70	80	75	72	70	78	74	72	69	68	
			0.56	1.0	86	81	77	74	85	80	77	74	83	79	76	74	82	78	76	73	72	
				1.25	89	84	81	78	88	84	81	78	86	82	80	78	84	81	79	77	76	
下方投影面積		c m ²	1.5	91	87	84	81	90	86	83	81	88	85	82	80	86	84	82	80	78		
等価発光面積			c m ²	2.0	93	90	87	85	92	89	87	85	90	88	86	84	89	87	85	83	82	
取付 高さ	器具間隔最大限		2.5	95	92	90	88	94	91	89	87	92	90	88	87	90	88	87	86	84		
	横方向 (A)		縦方向 (B)	3.0	96	94	92	90	95	93	91	89	93	91	90	88	91	90	88	87	85	
H m	0.42 H m	0.42 H m	4.0	97	95	94	92	96	95	93	92	94	93	92	90	92	91	90	89	87		
			5.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	91	88		
			7.0	99	98	97	96	98	97	96	95	96	95	94	94	94	93	93	92	90		
			10.0	100	99	98	97	99	98	97	96	96	96	95	95	95	94	94	93	91		

