

屋内照明器具特性	
品番 (品名)	XLGE1108
光源	LLD4000VCE1 ×1 845.0 lm
管理番号	K0176339 (0) DR 1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率		6 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		0 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		6 4 %																				
保守率		良 中 否	0 . 6 3	0 . 6	4 1	3 5	3 0	2 7	4 1	3 4	3 0	2 7	3 9	3 4	3 0	2 7	3 8	3 3	3 0	2 7	2 6	
			0 . 6	0 . 8	4 8	4 2	3 8	3 5	4 7	4 2	3 8	3 5	4 6	4 1	3 7	3 5	4 4	4 0	3 7	3 5	3 3	
			0 . 5 6	1 . 0	5 2	4 7	4 3	4 0	5 1	4 6	4 3	4 0	5 0	4 5	4 2	4 0	4 8	4 5	4 2	3 9	3 8	
				1 . 2 5	5 5	5 1	4 7	4 5	5 5	5 0	4 7	4 4	5 3	4 9	4 6	4 4	5 2	4 8	4 6	4 4	4 3	
下方投影面積		c m ²		1 . 5	5 8	5 4	5 0	4 8	5 7	5 3	5 0	4 7	5 5	5 2	4 9	4 7	5 4	5 1	4 9	4 7	4 5	
等価発光面積			c m ²	2 . 0	6 1	5 7	5 4	5 2	6 0	5 7	5 4	5 2	5 8	5 5	5 3	5 1	5 7	5 4	5 2	5 1	4 9	
取付 高さ	器具間隔最大限		2 . 5	6 2	5 9	5 7	5 5	6 1	5 9	5 7	5 5	6 0	5 8	5 6	5 4	5 8	5 6	5 5	5 3	5 2		
	横方向 (A) 縦方向 (B)			3 . 0	6 3	6 1	5 9	5 7	6 3	6 0	5 8	5 7	6 1	5 9	5 7	5 6	6 0	5 8	5 7	5 5	5 4	
H m	1 . 1 7 H m	1 . 1 7 H m	4 . 0	6 5	6 3	6 1	6 0	6 4	6 2	6 1	5 9	6 2	6 1	6 0	5 8	6 1	6 0	5 9	5 8	5 6		
			5 . 0	6 6	6 4	6 3	6 1	6 5	6 3	6 2	6 1	6 3	6 2	6 1	6 0	6 2	6 1	6 0	5 9	5 8		
			7 . 0	6 7	6 6	6 4	6 4	6 6	6 5	6 4	6 3	6 4	6 3	6 3	6 2	6 3	6 2	6 2	6 1	5 9		
			1 0 . 0	6 7	6 7	6 6	6 5	6 7	6 6	6 5	6 4	6 5	6 5	6 4	6 3	6 4	6 3	6 3	6 2	6 0		

