

屋内照明器具特性	
品番 (品名)	XLGE1030
光源	L LD2020LCE1 ×1 460.0 lm
管理番号	K0176348 (0) DR 1
BZ分類	BZ1

器具効率		91 %	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
					床	10 %				10 %				10 %				10 %				0 %		
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		91 %																						
保守率		良	0.6	77	72	69	66	77	72	69	66	76	71	68	66	75	71	68	66	65				
		中	0.8	83	78	75	72	82	78	75	72	81	77	74	72	79	76	74	72	71				
		否	0.6	86	82	79	76	85	81	78	76	84	80	78	76	82	79	77	76	74				
			0.56	1.0	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77			
下方投影面積		c m ²	1.25	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77				
等価発光面積			c m ²	1.5	90	87	84	82	89	86	84	82	88	85	83	82	86	84	82	81	80			
			2.0	92	90	88	86	92	89	87	85	90	88	86	85	88	87	85	84	82				
取付	器具間隔最大限		2.5	94	92	90	88	93	91	89	88	91	89	88	87	89	88	87	86	84				
高さ	横方向 (A)		縦方向 (B)	3.0	95	93	91	90	94	92	90	89	92	90	89	88	90	89	88	87	85			
H m	0.41 H m			4.0	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	89	86			
			5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	90	87				
			7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	91	88				
			10.0	98	97	96	96	97	96	95	95	95	94	94	93	93	92	92	92	89				

