

屋内照明器具特性

| | | | | | |
|---------|-----------------------------|--|--|--|--|
| 品番 (品名) | LGB19629B | | | | |
| 光源 | LED3500_70_465 x6 465.0 l m | | | | |
| 管理番号 | K0161568(0)DB1 | | | | |
| BZ分類 | BZ8/0.7/BZ7 | | | | |

| | | | | | | | | | | | | | | | | | | | | |
|--------|------------------------------------|----------|---------------|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|----|----|-----|----|
| 器具効率 | 100% | 天井 | 80% | | | | 70% | | | | 50% | | | | 30% | | | | 0% | |
| | | 壁 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 70 | 50 | 30 | 10 | 0% | |
| 上方光束 | 37% | 床 | 10% | | | | 10% | | | | 10% | | | | 10% | | | | 0% | |
| 下方光束 | 63% | 室指数 | 照明率 (X0.01) | | | | | | | | | | | | | | | | ZCM | |
| 保守率 | 良 中 否 0.63 0.6 0.56 | 0.6 | 46 | 34 | 26 | 20 | 43 | 32 | 24 | 19 | 37 | 28 | 21 | 17 | 32 | 24 | 19 | 15 | 10 | |
| | | 0.8 | 55 | 43 | 34 | 28 | 51 | 40 | 32 | 26 | 44 | 35 | 28 | 24 | 37 | 30 | 25 | 21 | 15 | |
| | | 1.0 | 61 | 49 | 40 | 34 | 57 | 46 | 38 | 32 | 49 | 40 | 34 | 29 | 42 | 35 | 29 | 25 | 19 | |
| | | 1.25 | 67 | 55 | 47 | 41 | 62 | 52 | 44 | 38 | 54 | 46 | 39 | 34 | 46 | 39 | 34 | 30 | 23 | |
| 下方投影面積 | c m ² | 1.5 | 71 | 60 | 52 | 46 | 66 | 57 | 49 | 43 | 57 | 50 | 44 | 39 | 49 | 43 | 38 | 34 | 26 | |
| | | 2.0 | 76 | 67 | 60 | 54 | 71 | 63 | 57 | 51 | 62 | 56 | 50 | 45 | 53 | 48 | 44 | 40 | 31 | |
| 取付高さ | 器具間隔最大限 | | 2.5 | 80 | 72 | 65 | 60 | 75 | 68 | 62 | 56 | 65 | 60 | 55 | 50 | 56 | 52 | 48 | 44 | 35 |
| | 横方向 (A) | 縦方向 (B) | 3.0 | 83 | 76 | 69 | 64 | 78 | 71 | 66 | 61 | 68 | 63 | 58 | 54 | 59 | 55 | 51 | 48 | 38 |
| H m | 1.48 H m | 1.48 H m | 4.0 | 86 | 80 | 75 | 70 | 81 | 76 | 71 | 67 | 71 | 67 | 63 | 60 | 62 | 59 | 56 | 53 | 42 |
| | | | 5.0 | 89 | 84 | 79 | 75 | 83 | 79 | 75 | 71 | 73 | 70 | 66 | 63 | 64 | 61 | 59 | 56 | 54 |
| | | | 7.0 | 91 | 87 | 84 | 80 | 86 | 83 | 79 | 76 | 76 | 73 | 71 | 68 | 67 | 64 | 62 | 60 | 48 |
| | | | 10.0 | 93 | 91 | 88 | 85 | 88 | 86 | 83 | 81 | 78 | 76 | 74 | 72 | 69 | 67 | 65 | 64 | 52 |

