

# 屋内照明器具特性

|         |                   |  |          |  |  |
|---------|-------------------|--|----------|--|--|
| 品番 (品名) | LGB57329W         |  |          |  |  |
| 光源      | LED3500_70_470 ×3 |  | 470.0 lm |  |  |
| 管理番号    | K0161569(0)DB1    |  |          |  |  |
| BZ分類    | BZ8/0.7/BZ7       |  |          |  |  |

|        |                  |          |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |    |    |    |
|--------|------------------|----------|------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----|----|----|
| 器具効率   | 100%             | 天井       | 80%              |      |      |      | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |    |    |    |
|        | 上方光束             |          | 37%              | 反射率  | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0% |    |    |
|        | 下方光束             |          | 63%              |      | 壁    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |    | 0% |    |
| 室指数    | 照明率 ( X0.01 )    |          |                  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      | ZCM  |    |    |    |
| 保守率    | 良                | 0.63     | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |    |    |
|        | 中                | 0.6      | 0.6              | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |    |    |    |
|        | 否                | 0.56     | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |    |    |
|        | 0.56             | 0.56     | 0.56             | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |    |    |    |
| 下方投影面積 | c m <sup>2</sup> |          | 1.25             | 67   | 55   | 47   | 40   | 62   | 52   | 44   | 38   | 53   | 45   | 39   | 34   | 45   | 39   | 34   | 29   | 25   | 18 | 14 | 10 |
|        | 等価発光面積           |          | c m <sup>2</sup> | 1.5  | 71   | 60   | 52   | 45   | 66   | 56   | 49   | 43   | 57   | 49   | 43   | 38   | 48   | 42   | 37   | 33   | 25 | 37 | 33 |
| 取付高さ   | 器具間隔最大限          |          | 2.5              | 80   | 72   | 65   | 59   | 75   | 68   | 61   | 56   | 65   | 59   | 54   | 50   | 56   | 51   | 47   | 44   | 34   | 47 | 44 | 34 |
|        | 横方向 (A)          | 縦方向 (B)  | 3.0              | 83   | 76   | 69   | 64   | 78   | 71   | 65   | 60   | 68   | 62   | 58   | 54   | 58   | 54   | 50   | 47   | 37   | 50 | 47 | 37 |
| H m    | 1.49 H m         | 1.50 H m | 4.0              | 86   | 80   | 75   | 70   | 81   | 76   | 71   | 66   | 71   | 67   | 63   | 59   | 61   | 58   | 55   | 52   | 41   | 55 | 52 | 41 |
|        |                  |          | 5.0              | 89   | 83   | 79   | 74   | 83   | 79   | 74   | 70   | 73   | 69   | 66   | 63   | 64   | 61   | 58   | 55   | 44   | 58 | 55 | 44 |
|        |                  |          | 7.0              | 92   | 87   | 84   | 80   | 86   | 82   | 79   | 76   | 76   | 73   | 70   | 68   | 66   | 64   | 62   | 60   | 47   | 66 | 64 | 47 |
|        |                  |          | 10.0             | 94   | 91   | 88   | 85   | 88   | 86   | 83   | 80   | 78   | 76   | 74   | 72   | 69   | 67   | 65   | 63   | 51   | 69 | 67 | 51 |

