

屋内照明器具特性

品番 (品名)	S F 9 1 8 W				
光源	LED2700_70_460 ×1 460.0 l m				
管理番号	K0161574 (0) DB 1				
B Z 分類	BZ8 / 0.7 / BZ7				

器具効率	101 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		38 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		63 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				ZCM
保守率	良	0.63	0.6	0.6	47	34	26	20	43	32	24	19	37	28	21	17	32	24	19	15	10
	中	0.6	0.8	0.6	55	43	34	28	51	40	32	26	44	35	28	23	37	30	25	20	15
	否	0.56	1.0	0.6	61	49	41	34	57	46	38	32	49	40	34	28	42	35	29	25	18
			1.25	0.6	67	56	47	40	62	52	44	38	54	45	39	34	46	39	34	30	22
下方投影面積	c m ²		1.5	71	60	52	46	66	57	49	43	57	49	43	38	49	43	38	33	25	
	等価発光面積		c m ²	2.0	77	68	60	54	72	63	56	51	62	55	50	45	53	48	43	39	30
取付高さ	器具間隔最大限		2.5	81	72	65	59	75	68	62	56	65	59	54	50	56	52	47	44	34	
	横方向 (A)	縦方向 (B)	3.0	83	76	70	64	78	71	66	61	68	63	58	54	58	54	51	47	37	
H m	1.49 H m	1.49 H m	4.0	87	81	75	70	82	76	71	67	71	67	63	59	62	58	55	52	41	
			5.0	89	84	79	75	84	79	75	71	74	70	66	63	64	61	58	55	44	
			7.0	92	88	84	80	87	83	79	76	76	73	70	68	67	64	62	60	47	
			10.0	94	91	88	85	89	86	83	81	79	76	74	72	69	67	65	63	51	

