

# 屋内照明器具特性

|         |                             |          |
|---------|-----------------------------|----------|
| 品番 (品名) | XND1001WW                   |          |
| 光源      | LED4000_85_1030 x1          | 1030.0lm |
| 管理番号    | K0158700(0)DB1              |          |
| BZ分類    | BZ2/1.1/BZ1/1.4/BZ2/8.5/BZ1 |          |

|        |                  |         |                  |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    |     |    |
|--------|------------------|---------|------------------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|----|-----|----|
| 器具効率   | 100%             | 天井      | 80%              |     |     |     | 70% |     |     |     | 50% |     |     |     | 30% |     |     |    | 0%  |    |
|        | 上方光束<br>0%       |         | 反射率              | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 70  | 50  | 30 | 10  | 0% |
| 下方光束   | 100%             | 床       |                  | 10% |     |     |     | 10% |     |     |     | 10% |     |     |     | 10% |     |    |     | 0% |
| 室指数    |                  |         | 照明率 ( X0.01)     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |    | ZCM |    |
| 保守率    | 良                | 0.81    | 0.6              | 70  | 61  | 55  | 51  | 69  | 61  | 55  | 51  | 67  | 60  | 55  | 51  | 66  | 59  | 54 | 51  | 49 |
|        | 中                | 0.77    | 0.8              | 80  | 72  | 66  | 62  | 79  | 71  | 66  | 62  | 77  | 70  | 65  | 62  | 75  | 69  | 65 | 61  | 60 |
|        | 否                | 0.68    | 1.0              | 86  | 78  | 73  | 69  | 84  | 78  | 73  | 69  | 82  | 77  | 72  | 69  | 80  | 75  | 71 | 68  | 67 |
|        |                  |         | 1.25             | 90  | 84  | 79  | 76  | 89  | 83  | 79  | 75  | 87  | 82  | 78  | 75  | 85  | 81  | 77 | 74  | 73 |
| 下方投影面積 | c m <sup>2</sup> |         | 1.5              | 93  | 88  | 83  | 80  | 92  | 87  | 83  | 80  | 90  | 85  | 82  | 79  | 88  | 84  | 81 | 78  | 77 |
|        | 等価発光面積           |         | c m <sup>2</sup> | 2.0 | 97  | 93  | 89  | 86  | 96  | 92  | 88  | 86  | 94  | 90  | 87  | 85  | 92  | 89 | 86  | 84 |
| 取付高さ   | 器具間隔最大限          |         | 2.5              | 100 | 96  | 93  | 90  | 98  | 95  | 92  | 89  | 96  | 93  | 91  | 88  | 94  | 91  | 89 | 87  | 85 |
|        | 横方向 (A)          | 縦方向 (B) | 3.0              | 101 | 98  | 95  | 93  | 100 | 97  | 94  | 92  | 98  | 95  | 93  | 91  | 95  | 93  | 91 | 90  | 87 |
| H m    | 1.16H m          | 1.16H m | 4.0              | 103 | 100 | 98  | 96  | 102 | 99  | 97  | 95  | 99  | 97  | 96  | 94  | 97  | 96  | 94 | 93  | 90 |
|        |                  |         | 5.0              | 104 | 102 | 100 | 98  | 103 | 101 | 99  | 98  | 101 | 99  | 98  | 96  | 98  | 97  | 96 | 95  | 92 |
|        |                  |         | 7.0              | 105 | 104 | 102 | 101 | 104 | 103 | 101 | 100 | 102 | 101 | 100 | 99  | 100 | 99  | 98 | 97  | 94 |
|        |                  |         | 10.0             | 106 | 105 | 104 | 103 | 105 | 104 | 103 | 102 | 103 | 102 | 101 | 100 | 101 | 100 | 99 | 99  | 96 |

