

屋内照明器具特性	
品番 (品名)	L G W 4 0 2 0 0
光源	L L D 4 0 0 0 M L C E 1 × 1 8 4 5 . 0 l m
管理番号	K 0 1 7 6 3 4 0 (0) D R 1
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2

器具効率		59 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 59 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.63	0.6	38	32	28	25	38	32	28	25	36	31	28	25	35	31	28	25	24	
			0.6	0.8	44	39	35	32	44	38	35	32	42	38	35	32	41	37	34	32	31	
			0.56	1.0	48	43	40	37	47	43	39	37	46	42	39	37	45	41	39	36	35	
				1.25	51	47	44	41	51	47	43	41	49	46	43	41	48	45	42	40	39	
下方投影面積		cm ²	1.5	53	50	47	44	53	49	46	44	51	48	46	44	50	47	45	43	42		
等価発光面積		cm ²	2.0	56	53	50	48	55	52	50	48	54	51	49	47	52	50	49	47	46		
取付 高さ	器具間隔最大限		2.5	58	55	53	51	57	54	52	51	55	53	52	50	54	52	51	49	48		
	横方向 (A)	縦方向 (B)	3.0	59	56	55	53	58	56	54	52	56	55	53	52	55	54	52	51	50		
H m	1.17 H m	1.17 H m	4.0	60	58	57	55	59	58	56	55	58	56	55	54	56	55	54	53	52		
			5.0	61	59	58	57	60	59	58	56	59	58	57	56	57	56	56	55	53		
			7.0	62	61	60	59	61	60	59	58	60	59	58	57	58	58	57	56	55		
			10.0	62	62	61	60	62	61	60	60	60	60	59	59	59	58	58	58	56		

